





VRF Air Conditioning System



INV2 DC Inverter Multi VRF System with its high-efficient inverter compressors has four exciting features which are different from those found on traditional inverter air conditioners: excellent energy-saving effect, more reliable and precise operation, smarter network control, providing users with best air conditioning experience.

CONTENTS

04 INV2

24 INV2 Mini & Slim

32 INV2 Heat Recovery

44 Indoor Units

64 Control System

82 Energy Recovery Ventilation (ERV)



INV2



Key Features

All DC Inverter Technology to Improve Compression Efficiency

All DC inverter compressor and high-performance high pressure chamber are adopted to reduce loss of overheat and improve compression efficiency from direct intake. Compared with low pressure chamber, the compression efficiency is inproved. High-efficient permasyn motor is adopted to provide better performance than traditional DC inverter compressor.

All DC Inverter Compressor

 All DC inverter compressor is used in this system. It can directly intake gas to reduce loss of overheat and improve efficiency.



• High-efficient permasyn motor is adopted to provide better performance than traditional DC inverter compressor.

• Technology of Maximum Torque Control with Minimum Current

It can reduce energy loss caused by device winding so as to realize higher efficiency.



Low-frequency Torque Control

It can directly control motor torque, through which fan motor can run at a low speed. Users will feel more comfortable while requirements of the system are also met.





• 180° Sine Wave DC Speed Varying Technology. It can satisfy various places' demands for different temperature and is able to save a great deal of electricity and provide users with utmost comfort at the same time.



Sensorless DC Inverter Fan Motor

• Stepless speed regulation ranges from 5Hz to 65Hz. Compared with traditioal inverter motors, the operation is more energy-saving.



 Sensorless control technology guarentees lower noise, less vibration and steadier operation.



Compact design

With compact design, the outdoor unit can be carried to the roof of building through elevator, with no need of crane. It is easier for delivery and installation.



88HP Max Capacity-The Largest Free Combination

Max capacity of single outdoor unit reaches 22HP and max combination capacity is even up to 88HP, in an industry leading level.

Max Combination capacity is extended to 88HP



Money is saved in system cost and piping



Non-polar CAN Technology to Improve Communication Efficiency

communication data.

Performance Index	Company A Multi-VRF Network	INV2 DC Inverter CAN Network		
	Software check	Hardware check, more reliable		
Reliability	One unit's communication error may lead to a breakdown of the whole network	If one unit has errors, it will exit from the network without any influence to other units.		
Or an and the Effective and	Low utilization	High utilization		
	Communication speed is about 10Kbps.	Communication speed is 20Kbps		
Compatibility	One main network, difficult to add new equipment	Multiple main networks, easy to add new equipment		
Communication Distance	1500m	1500m		

construction difficulties.





INV2

• Inventor is the first one to adopt non-polar CAN communication technology in the industry. CAN communication technology provides quicker system response speed, more convenient installation debugging and more reliable

• The non-polar CAN communication technology is applied to support flexible wiring installation, greatly reducing



Wide Range of Voltage and Operation Condition

Working voltage range of INV2 system has been improved to 320V~460V, which surpasses the national standard of 342V~420V. For places with insteady voltage, this system can still be running well.



Wide Applicable Location

INV2 can realize a combination of 4 outdoor unit modules connecting with as many as **80** indoor units. It's especially applicable for business building or hotels.



• Outdoor operation temperature range is improved

ing.

-5°C

-20°C

to -5°C~52°C in cooling and -20°C~24°C in heat-

52°C

24°C

Max.IDU Connection: 80 sets

Refrigerant Storage and Distribution

The INV2 system is designed without liquid receiver and the excess refrigerant is stored in the piping, which can minimize the refrigerant charging volume and enhance the control accurancy of refrigerant.



High Efficiency and More Energy Saving

Thanks to the advanced all DC inverter technology, optimized system design and accurate intelligent control technology, IPLV of **INV2** All DC Inverter Multi VRF System is up to 6.8.

New Generation of Energy-saving Operation Control Technology with Energy Saving Up to 20%

The **INV2** system has 2 modes for energy saving, which can be chosen to meet different electricity demands.

Mode 1:

In auto energy-saving mode, the system will self-adjust parameters according to the operation status, thus to lower the cost of electricity. Up to 15% of energy can be saved.

Mode 2:

In compulsory energy-saving mode, the system will limit power output forcibly. Up to 20% of energy can be saved.

Comfortable Heating

Advanced intelligent defrosting mode is adopted. Inventor advanced intelligent defrosting mode will choose the best defrosting way according to outdoor temperature and operation status to realize intelligent defrosting, effectively improving heating effect and performance. While in traditional defrosting mode, timing defrosting is adopted, which not only affects comfort but also reduces energy efficiency.









Accurate Intelligent Allocation Technology of Capacity and Output of Optimal Portion to Ensure Highest Efficiency

- When total load demands more than 75% of a running system's capacity, one more unit will automatically start;
- When total load demands less than 40% of a running system's capacity, one unit will automatically shut down:
- Therefore, each unit shares 40%-75% of the total load.
- Experiments show that an air conditioner costs the least energy when it's operating within 40%-75% of its capacity.

	company A	Inventor INV
Allocation Method	10HP(full load) + 2HP(low load)	6HP(partial load) + 6HP(partial load)
Performance Compared	Unit costs more energy and may be soon damaged.	Unit costs less energy and can always be kept in good condition.

Output of Optimal Portion to Ensure Highest Efficiency

The best heating or cooling performance can be realized in the most energy-saving way. DC inverter compressor and DC inverter fan will also be operating in this way to ensure high efficiency.



Sub-cooling Control Technology to Ensure Optimal Cooling and Heating

 Heat exchange loop can control the first subcooling process of heat exchanger. Subcooling degree can reach 11°C.



• Subcooling loop can realize 9 C second subcooling to guarantee cooling and heating performance.



Comfortable Design for A Better Life

The INV2 system has a wide range of working conditions. Whether it's in a cool winter or a hot summer, normal operation is guaranteed with the least noise, making users feel more comfortable.

Outdoor Unit Quiet Mode and Quiet Control

Quiet at night

The system can record the highest outdoor temperature. At night, the system will automatically turn to quiet mode. There are 9 quiet modes which can be set according to actual needs.

Quiet in compulsion

The system can also be set in this mode to ensure low noise as long as it is operating. Noise is as low as 45dB(A).



Quiet Control

After many times of CFD tests, a new fan bossing structure has been developed to reduce vibration of fan during running. Noise can be reduced by 3dB(A).

Compared with conventional fan, it can increase air volume by 12%, improving efficiency as well as lowering noise.

Temperature Controlled by Wired Controller with Higher Efficiency and More **Energy Saving**

Through setting temperature lower limit in cooling or dry mode, and setting temperature upper limit in heating, 3D heating or heat supply mode, the system is able to operate in a smaller temperature range so as to achieve energy saving.



Quiet Indoor Unit

The indoor unit of the INV2 system also adopts DC inverter motors to realize stepless regulation. According to indoor temperature or people's needs, users can set this mode through wired controller. Noise is as low as 22dB(A).



INV2 (Indoor

Fast Start-up in Heating

DC Compressor is first started to avoid too much electric current. Inverter compressor can operate in high frequency once starts up, so as to produce more heat.



7 Speeds Indoor Fan

Indoor fan speed can be set in 7 levels by wired controller. They are auto, low speed, medium-low speed, medium speed, medium-high speed, high speed and turbo. When the wired controller is on, press "FAN" button to set indoor fan speed circularly as below:



Excellent Performance Ensured by Advanced Technology

Through 10 years of research and development, Inventor INV2 has been further upgraded to a high level from electrical components, mechanical parts, control technology to communication technology.

Two-stage Oil Separation Control Technology (Patented)

First-stage oil separator adopts a filtration expansion valve with separation efficiency of 98%; Second-stage oil separator will separate the remained 2% refrigerant oil with separation efficiency of 95%. General oil separation efficiency reaches 99.9%.

Vil Return Control Technology

New Oil Return Control

Inventor new oil return control technology effectively controls system oil return and oil storage status of each compressor, which greatly improves the operation lifespan of compressor.



Specialized Compressor Oil Storage Control The system applies specialized compressor oil

storage technology, which can control the lowest oil level for compressor operation.







Vil Balance Control Technology

Oil Balance between Each Module

Based on the actual status of each module and compressor, the system can regulate compressor's operation and realize oil balance of each module.



Oil Balance between Each Compressor

Refrigerant is taken into the compressor by the suction pipe and then runs through the cooling system. It can control the oil level and minimum oil volume required by each compressor so as to realize oil balance between each compressor.



Modules Rotation Operating to Maximize Lifespan

Modules 8h rotation operating

The operating priority sequence of the outdoor unit modules will be changed without restart when the system accumulatively operates for 8 hours, which can maximize the service life of the system.



Intelligent Detection Control

Pressure Sensor Detection Control

Pressure sensor can precisely detect system high pressure and low pressure, and adjust output of fan and compressor, so as to make sure the system can work under the most energy-saving pressure condition.



Temperature Sensor Detection Control

Various temperature sensors are equipped to detect ambient temperature, indoor temperature and refrigerant's evaporating temperature, from which the operation status can be measured.

Multi Electronic Expansion Valves Control

Outdoor electronic expansion valve not only has throttling effect, but also control refrigerant flow. The system adopts multi electronic expansion valves control with total 960 grades regulated by two electronic expansion valves, so as to regulate refrigerant flow precisely and ensures reliable operation of system.



Smaller Impact to Power Grid

The start-up frequency of inverter compressor is gradually increased from 0Hz to the appointed operation frequency. The start-up current of compressor rotor is decreased by reducing load torque, hence impact to power grid during start-up is reduced and electromagnetic impact to compressor is reduced too.



Highly Anticorrosive Golden Fins

The primary material of Golden Fin is Al-Mn(Alumium-Manganese) anti-rust alloy, which is coated with the Golden Protection Layer(Components: Exoxy Resin & Modified Acrylic, Sillcon free), the anti-corrosice performance in salt-spray testing is 200%~300% higher than normal Blue Fin*.

Note: Satt-spary testing result is from INVENTOR materials chemistry testing laboratory.

Emergency Auto-Off Control

The outdoor unit can be linked with a fire alarm signal. In case of emergency, unit can automatically turn off to avoid risk or further loss.





Electricity Shortage Identification

The outdoor unit can receive a power signal of electricity shortage. In some places like first-class hotels, if diesel generator is used temporarily for providing electricity, outdoor unit will send the electricity shortage signal to indoor unit. In this case, only VIP rooms can be provided with air conditioning service.



Easy Installation for Various Kinds of Construction

ODU High Static Pressure Design

System has 4 levels of static pressure that can be set. Up to 82Pa pressure can be set for an outdoor unit. This design is especially useful when an outdoor unit needs to be placed indoor.

Excellent Emergency Operation Function to Ensure Reliable Operation

Emergency Function

The INV2 system can realize a combination of 4 outdoor unit modules. When error is occurred to one of the modules, the others will perform the emergency operation to sustain the air conditioning.



• Emergency Operation of Compressor

All the compressors in each single module are DC Inverter based, when one compressor has error, others will perform the emergency operation.

Emergency Operation of Fan

Double-fan design fan ensures that one fan can still work even if the other one has error.



1000m Pipe Design for Flexible Installation

INV2 system can be applied in different types of building construction. One of its advantages is the simple pipe design, which will simplify the installation and reduce installation cost.

- Max total pipe length reaches 1000m (with limitation)
- Actual pipe length between the outdoor unit and the farthest indoor unit: 165m
- Max height difference between indoor unit and outdoor unit: 90m

Note a: Distance between the first branch and the farthest indoor unit. b: Distance between the frist branch and the nearest indoor unit. a-b≤40m

Intelligent Debugging for Convenient Construction

INV2 has five auto debugging features:

- Automatic allocation of IDU and ODU addresses
- Automatic detection of IDU and ODU quantity
- Automatic detection of errors
- Automatic start-up of debugging
- Real-time judgment of pipe errors









Auto-refrigerant Recovery for Easy Maintenance

When auto refrigerant recovery function is set and cut-off valve of liquid pipe is closed during maintenance, the system will automatically operate compressor, EXV, solenoid valve and fan, etc. Taking advantage of compressor power, the refrigerant is recovered at the condensing side of outdoor unit to achieve environmental effect. Meanwhile, system low pressure is displayed simultaneously during refrigerant recovery.



Inspection Window for Convenient Checking

Inspection window is available for guick checking of system operation status. No need to open panel for checking, which will be more time-saving and easier for maintenance.



Flexible Wiring

Common wire can meet the communication demand with no need of specialized communication wire. Common sheath twisted pair cable can be used as there is no polarity requirement.



COMPANY A



Common Plastic Electricity Wire



INV2



Inventor INV2 provides hotels with unique season setting function and key-card control function.

Season Setting

Cooling or heating mode can be deactivated during a certain season to avoid affecting unit's normal operation due to mode conflict.

Key-card Control for Hotel Management

The unit can be turned on or off by inserting or removing the key-card. When the key-card is removed, the system can remember all the setting and stop operation. When the key-card is inserted back, the system will be under standby mode or operate according to the status before removing key-card. It is well suited to hotels, restaurants, etc.



Auto Addressing of Outdoor and Indoor Unit

CAN network is adopted to achieve auto addressing of outdoor and indoor unit. It can allocate IDU and ODU addresses and detect IDU and ODU quantity, which greatly improves construction efficiency.





SPECIFICATIONS & PARAMETER OF OUTDOOR UNITS

Voutdoor Units Lineup

MO	DEL	INV2-224M1T (8HP)	INV2-280M1T (10HP)	INV2-335M1T (12HP)	INV2-400M1T (14HP)	INV2-450M1T (16HP)
1.0000 (b)	INV2-224M1T (8HP)	٠				
	INV2-280M1T (10HP)		۲			
R	INV2-335M1T (12HP)			٠		
	INV2-400M1T (14HP)				۲	
(in the set	INV2-450M1T (16HP)					•
	INV2-504M1T (18HP)	٠	۲			
	INV2-560M1T (20HP)					
	INV2-615M1T (22HP)		٠	٠	10780700100	19110110117
	INV2-680M1T (24HP)		٠		۲	
التعريم المتر	INV2-730M1T (26HP)		٠			٠
	INV2-785M1T (28HP)			۲		٠
	INV2-850M1T (30HP)				٠	٠
₩ <u>─</u> ┙└──┥┟═╼┥└──┥	INV2-900M1T (32HP)					
	INV2-960M1T (34HP)					
	INV2-1010M1T (36HP)					٠
diam 11 Ben 11 Ben 1	INV2-1065M1T (38HP)		٠	٠		
	INV2-1130M1T (40HP)		٠		٠	٠
Constraints of the second s	INV2-1180M1T (42HP)		۲			••
I then if then it then t	INV2-1235M1T (44HP)			٠		
	INV2-1300M1T (46HP)				۲	
	INV2-1350M1T (48HP)					-
	INV2-1410M1T (50HP)					•
	INV2-1460M1T (52HP)					
	INV2-1515M1T (54HP)		•	•		••
	INV2-1580M1T (56HP)		٠		۲	
	INV2-1630M1T (58HP)		۲			*
	INV2-1685M1T (60HP)			۲		-
	INV2-1750M1T (62HP)					-
And the second location of the second s	INV2-1800M1T (64HP)					**

Specifications of Outdoor Units 380~415V,50/60Hz

Mode	6		INV2- 224M1T	INV2- 280M1T	INV2- 335M1T	INV2- 400M1T	INV2- 450M1T	INV2- 504M1T*1	INV2- 560M1T*1	INV2- 615M1T**
Capacity range		HP	8	10	12	14	16	18	20	22
Conacity	Cooling	kW	22.4	28	33.5	40	45	50.4	56	61.5
Capacity	Heating	kW	25	31.5	37.5	45	50	56	63	69
EER		kW/kW	4.31	4	3.98	3.76	3.56	3.38	2.97	2.75
COP		kW/kW	4.55	4.32	4.17	4.05	3.85	3.84	3.6	3.16
Power supply		V/Ph/Hz				380~415V-3	Ph-50/60Hz			
Max. Circuit/Fu	se Current	A	15.7/20	20.9/25	24.7/32	28.8/40	33.2/40	36.8/40	43.8/50	48.9/50
Power	Cooling	kW	5.2	7	8.41	10.65	12.65	14.9	18.9	22.3
comsumption	Heating	kW	5.5	7.3	9	11.1	13	14.6	17.5	21.8
Maximum drive	IDU NO.	unit	13	16	19	23	26	31	34	38
Refrigerant Cha	arge volume	kg	5.9	6.7	8.2	9.8	10.3	12.7	13	13.5
Sound pressure	e level	dB(A)	60	61	63	63	63	65	66	66
	Liquid	mm	Φ9	.52		Φ12.7			Φ15.9	
Connecting	Gas	mm	Φ19.05	Φ22.2	Φ2	5.4	Φ28.6		Φ28.6	
hibe	Oil balance	mm			Φ9.52				Φ9.52	
Dimension	Outline	mm	930*76	5*1605		1340*765*1605			1340*765*1740	
(W*D*H)	Package	mm	1010*84	40*1775		1420*840*1775			1420*840*1910	
Net weight/Gro	ss weight	kg	225/235	225/235	285/300	360/375	360/375	400/415	400/415	400/415
Loading	40' GP	set	24	24	16	16	16	16	16	16
quantity	40' HQ	set	24	24	16	16	16	16	16	16

Specifications of ODU Combination

380~415V,50/60Hz

		Cooli Capa	ng city	Pow	er t	Dimension/MED+U	Airflow	ESD	Noice	Noise at Night	Connec pipe dia	ting meter	Oil	Min.	Max.	Woight
Model	Power Supply	Cooling	Heating	Cooling	Heating	Dimension(W D H)	Volume	ESP	Noise	Operation Noise	Liquid	Gas	Pipe	current	current	weight
		kW	kW	kW	kW	mm	m²/h	Pa	dB(A)	dB(A)	mm	mm	mm	A	A	kg
INV 2-504M1T		50.4	56.5	12.2	12.8	2×(930×765×1605)	2×11400	0~82	64	45	Φ15.9	Ф28.6	Φ9.52	36.6	40	225×2
INV 2-560M1T		56	62.5	14	14.6	2×(930×765×1605)	2×11400	0~82	64	45	Φ15.9	Ф28.6	Φ9.52	41.8	50	225×2
INV 2-615M1T		61.5	69	15.41	16.3	(930×765×1605)+(1340×765×1605)	11400+14000	0~82	65	45	Φ15.9	Ф28.6	Φ9.52	49.7	50	285+225
INV 2-680M1T		68	76.5	17.65	18.4	(930×765×1605)+(1340×765×1605)	11400+14000	0~82	65	45	Ф15.9	Ф28.6	Φ9.52	54.1	63	225+360
INV 2-730M1T		73	81.5	19.65	20.3	(930×765×1605)+(1340×765×1605)	11400+14000	0~82	65	45	Ф19.05	Ф31.8	Ф9.52	57.9	63	225+360
INV 2-785M1T		78.5	87.5	21.06	22	2×(1340×765×1605)	2×14000	0~82	66	45	Ф19.05	Ф31.8	Ф9.52	66.1	80	285+360
INV 2-850M1T		85	95	23.3	24.1	2×(1340×765×1605)	2×14000	0~82	66	45	Φ19.05	Ф31.8	Φ9.52	66.4	80	360×2
INV 2-900M1T		90	100	25.3	26	2×(1340×765×1605)	2×14000	0~82	66	45	Φ19.05	Ф31.8	Φ9.52	66.5	80	360×2
INV 2-960M1T		96	108	24.65	25.7	2×(930×765×1605)+(1340×765×1605)	2×11400+14000	0~82	67	45	Ф19.05	Ф31.8	Φ9.52	70.6	80	225×2+360
INV 2-1010M1T	380~ 415V- 3Ph-	101	113	26.65	27.6	2×(930×765×1605)+(1340×765×1605)	2×11400+14000	0~82	67	45	Ф19.05	Ф38.1	Φ9.52	75	80	225×2+360
INV 2-1065M1T	50/60Hz	106.5	119	28.06	29.3	(930×765×1605)+2×(1340×765×1605)	11400+2×14000	0~82	67	45	Φ19.05	Ф38.1	Φ9.52	78.8	100	225+285+360
INV 2-1130M1T		113	126.5	30.3	31.4	(930×765×1605)+2×(1340×765×1605)	11400+2×14000	0~82	67	45	Ф19.05	Φ38.1	Φ9.52	82.9	100	225+360×2
INV 2-1180M1T		118	131.5	32.3	33	(930×765×1605)+2×(1340×765×1605)	11400+2×14000	0~82	67	45	Ф19.05	Ф38.1	Φ9.52	87.3	100	225+360×2
INV 2-1230M1T		123.5	137.5	33.71	35	3×(1340×765×1605)	3×14000	0~82	68	45	Ф19.05	Ф38.1	Ф9.52	91.1	125	285+360×2
INV 2-1300M1T		130	145	35.95	37.1	3×(1340×765×1605)	3×14000	0~82	68	45	Φ19.05	Ф38.1	Ф9.52	95.2	125	360×3
INV 2-1350M1T		135	150	37.95	39	3×(1340×765×1605)	3×14000	0~82	68	45	Ф19.05	Ф38.1	Φ9.52	99.6	125	360×3
INV 2-1410M1T		141	158	37.3	38.7	2×(930×765×1605)+2×(1340×765×1605)	2×11400+2×14000	0~82	69	47	Φ22.2	Ф44.5	Φ9.52	103,8	125	225×2+360×2
INV 2-1460M1T		146	163	39.3	40.6	2×(930×765×1605)+2×(1340×765×1605)	2×11400+2×14000	0~82	69	47	Φ22.2	Ф44.5	Ф9.52	108.2	125	225×2+360×2
INV 2-1515M1T		151.5	169	40.71	42.3	(930×765×1605)+3×(1340×765×1605)	11400+3×14000	0~82	69	47	Φ22.2	Φ44.5	Ф9.52	112.0	125	225+285+360×2
INV 2-1580M1T		158	176.5	42.95	44.4	(930×765×1605)+3×(1340×765×1605)	11400+3×14000	0~82	69	47	Ф22.2	Ф44.5	Ф9.52	116.1	125	225+360×3
INV 2-1630M1T		163	181.5	44.95	46.3	(930×765×1605)+3×(1340×765×1605)	11400+3×14000	0~82	69	49	Φ22.2	Ф44.5	Ф9.52	120.5	160	225+360×3
INV 2-1685M1T		168.5	187.5	46.36	48	4×(1340×765×1605)	4×14000	0~82	70	49	Φ22.2	Φ44.5	Ф9.52	124.3	160	285+360×3
INV 2-1750M1T		175	195	48.6	50.1	4×(1340×765×1605)	4×14000	0~82	70	49	Φ22.2	Φ44.5	Φ9.52	128.4	160	360×4
INV 2-1800M1T		180	200	50.6	52	4×(1340×765×1605)	4×14000	0~82	70	49	Ф22.2	Ф44.5	Φ9.52	132.8	160	360×4

INV2 Mini & Slim



Key Features

All DC Inverter Technology to Improve Compression Efficiency

All DC inverter compressor and high-performance high pressure chamber are adopted to reduce loss of overheat and improve compression efficiency from direct intake. Compared with low pressure chamber, the compression efficiency is inproved. High-efficient permasyn motor is adopted to provide better performance than traditional DC inverter compressor.

All DC Inverter Compressor

 All DC inverter compressor is used in this system. It can directly intake gas to reduce loss of overheat and improve efficiency.

• High-efficient permasyn motor is adopted to provide better performance than traditional DC inverter compressor.

• Technology of Mximum Torque Control with Minimum Current

It can reduce energy loss caused by device winding so as to realize higher efficiency.



• Low-frequency Torque Control

It can directly control motor torque, through which fan motor can run at a low speed. Users will feel more comfortable while requirements of the system are also met.





 180° Sine Wave DC Speed Varying Technology. It can satisfy various places' demands for different temperature and is able to save a great deal of electricity and provide users with utmost comfort at the same time.



Sensorless DC Inverter Fan Motor

- Stepless speed regulation ranges from 5Hz to 44Hz. Compared with traditioal inverter motors. the operation is more energy-saving.
- Sensorless control technology guarentees lower noise. less vibration and steadier operation.



Refore

Sensorless DC Inverter Fan Motor

The indoor unit adopts high-efficiency brushless DC motor. Compared with conventional motor, the wfficiency of brushless DC motor is improved by more than 30%. Meanwhile, the design of evaporation capacity flow is optimized through emulation software of refrigeration system and the heat exchange amount of evaporator is greatly improved.

High-efficiency Digital PFC Control*

High-efficiency PFC control technology is adopted with efficiency improved by about 1% compared with conventional PFC. For the air conditioner with rated power of 5kW, 50W of electricity can be saved every hour and 1.2kW of electricity can be saved every day.

*This feature applicable for INV2 Mini only.

Wider Operation Condition Range

The unit adopts DC motor with more accurate high pressure control, which effectively solves the high pressure control problem in low ambient temperature cooling. So the operation range in cooling is wider.



Comfortable and Quiet Mode

Low Noise of Outdoor Unit

- The advanced sub-cooling control technology is applied to reduce the liquid flow noise of indoor unit in cooling operation.
- Noise of outdoor unit can be as low as 45dB thanks to noise optimized design or fan system and compressor system, and multiple kinds of quiet modes of outdoor unit.

Low Noise of Indoor Unit

- The pioneering and patented high-efficiency centrifugal fan blade and low-noise volute are adopted. Meanwhile, the imported silent valve is adopted to reduce noise of entire unit as low as 22db(A).
- By adopting the optimal inlet angle of centrifugal fan blade and optimal diameter ratio between internal and external circles of impeller, the air volume is increased and fan noise is decreased greatly.
- The advanced supercooling control technology and the oil-return technology under heating mode has efficiently solved the problem of liquid flow noise of indoor unit, which improved the sound quality of indoor unit.

Intelligent Temperature Control Technology

Intelligent temperature control technology is adopted for super fast cooling or heating, so that indoor temperature will reach set temperature more quickly.





Efficiency comparison between Inventor high efficiency PFC and conventional PFC

Efficiency of Inventor high-efficiency PFC

Power output(w)

4000

3000

Efficiency of conventional PEC

6000

5000

Efficiency

99.00%

98.00% 97.00%

96.00%

95.00%

94.00%

93.00%

1000

2000

Curve of load characteristics

INV2 Mini

INV2 Slim

Comfortable Heating

Advanced intelligent defrosting mode is adopted. Inventor advanced intelligent defrosting mode will choose the best defrosting way according to outdoor temperature and operation status to realize intelligent defrosting, effectively improving heating effect and performance. While in traditional defrosting mode, timing defrosting is adopted, which not only affects comfort but also reduces energy efficiency.

Non-commutative Oil Return Technology in Heating

The unit can achieve non-commutative oil return in heating when outdoor ambient temperature is within 0~20°C. Thanks to this technology, indoor ambient temperature is more stable and comfort is improved in heating mode.

Reliable Operation

Compressor Closed-loop Startup Technology with More Reliable Startup

The self-innovative closed-loop startup control technology is adopted. Thanks to this technology, the startup current is small and startup is more reliable.

High Anti-interference Ability

The latest CAN bus communication technology is adopted, with non-polar communication and high anti-interference ability. Common communication wire can meet the communication demand with no need of specialized shielded wire. The customers can buy the communication wire by themselves, greatly reducing installation difficulties.

Advanced High-frequency Transformer with More Stable Voltage

- The advanced switching power supply is adopted with lower power consumption and higher power efficiency.
- Wide voltage-regulation range ensures stable voltage output when the voltage of grid fluctuates.
- Compared with conventional transformer, the size of high-frequency transformer is small and the weight is light.

Ultra-long Connection Pipe for More Convenient Connection

Under the subcooling control technology gained by adding subcooler, the indoor unit and outdoor unit of INV2 mini can operate reliably with longer connection pipe.

	Company A	Inventor INV2 Slim	Inventor INV2 Mini
Total piping length	150m	300m	300m
Equivalent piping length	70m	100m	150m

Top Advanced Light and Compact Size

INV2 slim adopts small and compact size design. The dimension of the unit is 1430(H)×940(W) ×320(D). Compared with the normal product with the same capacity, size and weight are reduced a lot.

Easy Installation with Lower Construction Cost

The outdoor unit of INV2 slim is with small size and light weight. No need fork lifter and crane for movement and installation

Movement by Stairs and Elevator

The outdoor unit of INV2 slim is with compact and small size for saving space and easy movement. It can be carried by elevator or stairs.

INV2 Mini & Slim Line Up

Mini Line up HP Model Product Outlook INV2-H120N1S 4 INV2-H140N1S 5

INV2-H160N1S

Mini 50/60 Hz

6

	Model		INV2-H120N1S*1	INV2-H140N1S*1	INV2-H160N1S*1
Capacity range		HP	4	5	6
Conseitu	Cooling	kW	12.1	14	16
Capacity	Heating	kW	14	16.5	18.5
EER		W/W	3.97	3.52	3.3
COP		W/W	4.28	4.14	3.96
Power st	upply	V/Ph/Hz		220~240V-1Ph-50Hz&208~230V-1Ph-60Hz	
Max. Circuit/Fu	se Current	A	28.1/32	31.8/32	33.6/40
Power	Cooling	kW	3.05	3.98	4.85
comsumption	Heating	kW	3.27 3.99		4.67
Maximum drive	IDU NO.	unit	7	8	9
Refrigerant Cha	arge volume	kg	5	5	5
Sound pressure	e level	dB(A)	55	56	58
Connecting	Liquid	mm		Φ9.52	
pipe	Gas	mm	Φ15	.87	Φ19.05
Dimension	Outline	mm		900*340*1345	
(W*D*H)	Package	Package mm 998*458*1515		998*458*1515	
Net weight/Gro	ss weight	kg	110/120	110/120	110/120
Loading	40' GP	set	57	57	57
quantity	40' HQ	set	57	57	57

*1. This series outdoor unit cannot match with US air handler, fresh air processing unit and high static ESP duct type unit.

VSlim 50/60 Hz

Model		INV2-H200N1T*2	INV2-H224N1T*2	INV2-H250N1T*2	INV2-H280N1T*2	INV2-H308N1T*2	INV2-H335N1T*2	
Capacity range		HP	7	8	9	10	11	12
Conocity	Cooling	kW	20.0	22.4	24.5	28.0	30.8	33.5
Capacity	Heating	kW	22.4	25.0	26.0	31.5	33.9	37.5
EER		W/W	3.1	3.1	3.1	2.97	2.99	3.04
COP		W/W	4.0	4.1	3.7	3.66	3.59	3.60
IPLV	Cooling	kW/kW	6.1	6.1	6.0	6.0	6.0	6.0
Power supply		V/Ph/Hz			380-415~3	Ph~50/60Hz		
Max. Circuit/Fu	ise Current	A	25	25	25	25	25	25
Power	Cooling	kW	6.5	7.2	8.0	9.4	10.3	11.0
comsumption	Heating	kW	5.6	6.1	7.0	8.6	9.6	10.4
Maximum drive	IDU NO.	unit	12	13	15	17	18	20
Refrigerant Ch	arge volume	kg	5.5	5.5	6.0	7.5	8.0	8.0
Sound pressur	e Cooling	dB(A)	57	58	59	59	59	60
level	Heating	dB(A)	58	59	60	60	60	61
Connecting	Liquid	mm	Φ9.52	Φ9.52	Φ9.52	Φ12.7	Φ12.7	Φ12.7
pipe	Gas	mm	Φ19.05	Φ19.05	Φ19.05	Φ25.4	Φ25.4	Φ25.4
Dimension	Outline	mm	940*320*1430	940*320*1430	940*320*1430	940*460*1615	940*460*1615	940*460*1615
(W*D*H)	Package	mm	1033*433*1580	1033*433*1580	1033*433*1580	1033*573*1765	1033*573*1765	1033*573*1765
Net weight/Gro	ss weight	kg	133/144	133/144	133/144	160/175	165/180	175/185
Loading	40' GP	set	54	54	54	44	44	44
quantity	40' HQ	set	54	54	54	44	44	44

Tote: (1) Testing conditions of rated cooling capacity: indoor 27°CDB/19°CWB, outdoor 35°CDB, connection pipe length of 5m, no height difference between units. (2) Testing conditions of rated heating capacity: indoor 20°CDB, outdoor 7°CDB/6°CWB, connection pipe length of 5m, no height difference between units.

3 The total indoor unit capacity shall be within 50% to 130% of outdoor unit capacity. Correction of other parameters can be referred to the unit capacity correction sheet. ④ The above-mentioned parameters are tested with standard connection pipe length. In actual engineering, please arrange correction according to the capacity correction with long connection pipe.

*2: This product is under development. The parameters are estimated, please refer to the value on the nameplate

Slim I	Line up	
HP	Model	Product Outlook
7	INV2-H200N1T	
8	INV2-H224N1T	
9	INV2-H250N1T	
10	INV2-H280N1T	
11	INV2-H308N1T	
12	INV2-H335N1T	

INV2 Heat Recovery

Key Features

High Efficiency

INV2 Heat Recovery System embodies the excellent features of INV2 (DC inverter technology, DC fan linkage control, precise control of capacity output, balancing control of refrigerant, original oil balancing technology with high pressure chamber, high-efficiency output control, low-temperature operation control technology, super heating technology, high adaptibility for project, environmental refrigerant). Its energy efficiency is improved by 78% compared with conventional multi VRF.

All DC Inverter Technology to Improve Compression Efficiency

• All DC inverter compressor is used in this system. It can directly intake gas to reduce loss of overheat and improve efficiency.

• High-efficient permasyn motor is adopted to provide better performance than traditional DC inverter compressor.

High Pressure Chamber Design

What's high pressure chamber?

The low temperature and low pressure refrigerant gas inhaled from the suction inlet of compressor will change to high-temperature and high-pressure gas after compression by scroll plate. Then the gas will go out from the exhaust at the center of fixed scroll and get into lower chamber of compressor, so that the chamber of compressor is in high temperature and high pressure.

What's the benefits of high pressure chamber?

High pressure chamber compressor inhales directly to reduce overheat suction loss and improve compression efficiency.

Sensorless DC Inverter Fan Motor

Stepless speed regulation ranges from 5Hz to 65Hz. Compared with traditioal inverter motors, the operation is more energy-saving.

Sensorless control technology guarentees lower noise, less vibration and steadier operation.

Wide Range of Voltage to Ensure a Steady Running

Working voltage range of INV2 system has been improved to 320V~460V, which surpasses the national standard of 342V~420V. For places with insteady voltage, this system can still be running well.

Wide Applicable Location

cially applicable for business building or hotels.

INV2 can realize a combination of 4 outdoor unit modules connecting with as many as 80 indoor units. It's espe-

Max.IDU Connection: 80 sets

Comfortable Design for A Better Life

Intelligent Quiet Function at Night

• Quiet at night

Intelligently adjustment of outdoor fan control can minimize the noise during night time. Up to 8dB(A) can be reduced and operation noise at night is as low as 50dB(A).

Low noise design

HP Chamber compressor has lower exhaust pressure fluctuation so that noise is lower.

The optimized design of condensing fan blade reduces the air flow turbulence among blades, so that the noise is lower.

Vide Operation Range

The unit can operates in wide range, greatly reducing the ambient temperature limitation.

Note

If the required capacity of indoor units is 50% higher than outdoor unit, cooling range may be lower to -15°C.

If the required capacity of indoor units is 50% higher than outdoor unit,cooling range may be up to -5°C

Comfortable Heating

Advanced intelligent defrosting mode is adopted. Gree advanced intelligent defrosting mode will choose the best defrosting way according to outdoor temperature and operation status to realize intelligent defrosting, effectively improving heating effect and performance. While in traditional defrosting mode, timing defrosting is adopted, which not only affects comfort but also reduces energy efficiency.

Individual Control for More Energy Saving

The set temperature of each room may vary by the individual thermostat control of each indoor unit. The cooling and heating operation can be performed at the same time.

35

Excellent Performance Ensured by Advanced Technologyn

Modules Rotation Operating to Maximize Lifespan

Modules 8h rotation operating

The operating priority sequence of the outdoor unit modules will be changed without restart when the system accumulatively operates for 8 hours, which can maximize the service life of the system.

Excellent Emergency Operation Function to Ensure Reliable Operation

Emergency Function

The INV2 system can realize a combination of 4 outdoor unit modules. When error is occurred to one of the modules, the others will perform the emergency operation to sustain the air conditioning.

• Emergency Operation of Compressor

All the compressors in each single module are DC Inverter based, when one compressor has error, others will perform the emergency operation.

 Emergency Operation of Fan Double-fan design ensures that one fan can still

work even if the other one has error.

Highly Anticorrosive Golden Fins

The primary material of Golden Finis Al-Mn(Alumium-Manganese) anti-rust alloy, which is coated with the Golden Protection Layer(Components: Exoxy Resin & Modified Acrylic, Sillcon free), the anti-corrosice performance in salt-spray testing is 200%~300% higher than normal Blue Fin*.

Oil Return Control Technology

New Oil Return Control

Inventor new oil return control technology effectively controls system oil return and oil storage status of each compressor, which greatly improves the operation lifespan of compressor.

• Specialized Compressor Oil Storage Control The system applies specialized compressor oil storage technology, which can control the lowest oil level for compressor operation.

Without External Oil-balanced Pipe Design

The unit is without external oil-balanced pipe design, reducing system pipeline connection and easy for engineering installation. The system will allocate lubricating oil of each module according to its demand, which is more intelligent, more efficient and more equal.

Easy Installation and Maintenance

Compact Design

With compact design, the outdoor unit can be carried to the roof of building through elevator, with no need of crane. It is easier for delivery and installation.

Easy Maintenance

checking, which will be more time-saving and easier for maintenance.

Error Display & Self-diagnostic Function

Through LED display(different combinations of ON, OFF, or BLINK) on the main board, the malfunction can be judged.

Easy Transportation

Optimized base frame

Optimized base frame, the locating and fixing of the outdoor unit during installation is more convenient and reliable.

Transportable by forklift

• Five-way piping connection

Piping and wiring are availiable to the front and back, left and right, and bottom.

The five-waypiping connection reduces installation difficulty and cost, improves the installation efficiency.

• Inspection window is available for quick checking of system operation status. No need to open panel for

INV2 HR Line Up

F HR Line up

HP	Model	Product Outlook
8HP	INV2-HR224M1T	
10HP	INV2-HR280M1T	
12HP	INV2-HR335M1T	
14HP	INV2-HR400M1T	
16HP	INV2-HR450M1T	No. of Concession, Name

Specifications and Parameters 50/60 Hz

	Model		INV2-HR224M1T	INV2-HR280M1T	INV2-HR335M1T	INV2-HR400M1T	INV2-HR450M11	
Capacity rang	e	HP	8	10	12	14	16	
Descentification of the second	Cooling	kW	22.4	28	33.5	40	45	
Japacity	Heating	kW	25	31.5	37.5	45	50	
ER		W/W	4.07	3.73	3.76	3.54	3.33	
COP		W/W	4.17	3.89	3.68	3.85	3.62	
PLV	Cooling	kW/kW	1	/	I	1	1	
ower Supply		V/Ph/Hz		380-	~415V-3Ph-50/60Hz			
/lax. circuit/fu	se current	A	15.7/20	20.9/25	24.7/32	28.8/40	33.2/40	
ower	Cooling	kW	5.5	7.5	8.9	11.3	13.5	
omsumption	Heating	kW	6	8.1	10.2	11.7	13.8	
/laximum driv	e IDU NO.	unit	13	16	19	23	26	
Refrigerant Cl	harge volume	kg	6.2	7.1	8.6	10.2	10.5	
Sound pressu	ire level	dB(A)	60	61	63	63	63	
`onnecting	Liquid	mm	Φ9.	52		Φ12.7		
ine	Gas(Low pressure	mm	Φ19.05	Φ22.2	Φ25	.4	Φ28.6	
ipe	Gas(High pressure	mm		Ф19.05		Φ2	2.2	
Dimension	Outline	mm	930*76	5*1605		1340*765*1605		
W*D*H)	/*D*H) Package mm		1010*84	0*1775	1420*840*1775			
Net weight/	Gross weight	kg	233/243	233/243	303/318	360/375	360/375	
.oading	40' GP	set	24	24	16	16	16	
uantity	40' HQ	set	24	24	16	16	16	

50 Hz

Mod	el		INV2-MEU11	INV2-MEU41	INV2-MEU81		
Max.IDU Branches		unit	1	4	8		
No. of connectable II	DU of each branch	unit	8	8	8		
Total Connectable II	DU	unit	8	32	64		
Max. Capacity of eac	ch branch	kW/kW	14	14	14		
Max. Capacity of connectable IDU		kW/kW	14	45	65		
Power supply V/Ph/Hz			220-240V-1Ph-50Hz				
Power comsumption		W	20	30	30		
Maximum drive IDU	NO.	unit	1	4	8		
0.444.4411-34	Liquid	mm	Φ9.52	Φ12.7	Φ15.9		
Disias Cossociation	Gas(Low pressure)	mm	Φ15.9	Φ22.2	Φ22.2		
Piping Connection	Gas(High pressure)	mm	Φ19.05	Φ28.6	Φ28.6		
Indoor Unit Piping	Liquid	mm	Φ9.5	Φ9.5	Φ9.5		
Connection	Gas	mm	Φ15.9	Φ15.9	Φ15.9		

Key Features of Indoor Units

F High Static Pressure Duct Type Indoor Unit

· High static pressure design

Static pressure can be up to 150Pa, especially suitable for places in need of long distance airflow.

Easy maintenance

The system has maintenance port for easy maintenance.

Convenient installation

You can choose circular air duct or rectangular air duct according to actual needs. Or you can choose different ways of air return.

Protection function

Anti-freezing protection, fan motor overload protection, temperature sensor malfunction protection.

Low Static Pressure Duct Type Indoor Unit

• Low static pressure, low noise

Especially suitable for rooms of compact structure or small installation space. Also, it provides you with a comfortable and quiet living environment.

Intelligent drainage device

Water height difference up to 1.0m, which can effectively drain out condensing water and save space.

Note: Please specify if you need this function.

Convenient installation

Tab type plastic filter, detachable fan motor, independent water pump assembly and electric box assembly, all for convenient maintenance.

Protection function

Water overflow protection, anti-freezing protection, fan motor overload protection, temperature sensor malfunction protection.

Slim Duct Type Indoor Unit

Highly Efficient & Energy-saving

High-efficiency DC brushless motor is used. Its efficiency is improved by over 30% compared with common motor. Evaporator flow path adopts simulating optimized design via the refrigeration system simulation software, which has greatly increased the heat exchange capacity of evaporator.

Slim & Small

The unit is only 200mm's thick and 450mm's deep. Suspended ceiling doesn't have to be very high. It is suitable for ordinary rooms.

• Wiring of Electric Control Box

Mounting board of electric control box elements are arranged at both sides of the mounting board of fan motor. There is a wire-cross notch on each side so that wiring at both sides of the mounting board of fan motor is convenient and efficient. Strong and weak current are also separated to ensure the effectiveness of weak current signal transmission.

Protection Functions

Anti-freezing protection, fan motor built-in overload protection, temperature sensor error protection

• Ultra-quiet

High-efficiency centrifugal fan and ultralow noise volute are developed with ANSYS and Fluent. They have also gained national patents. Meanwhile, inlet mute valve is adopted so that noise of the complete unit is greatly reduced.

Fast & Strong

Intelligent temperature control technology is adopted. Cooling/ Heating function is fast and strong so that room temperature can quickly reach set temperature.

• Flexible Installation

Based on the requirements of building and utilization, different ways of air return and different air supply static pressure can be selected.

CAN Bus Communication Technology

System response speed is faster and communication is more reliable. Auto addressing, non-polar communication, free wire matching

Convenient Operation & Maintenance

Electric control box is attached independently so that it can be detached as a whole, which is convenient for maintenance. The installation and maintenance of fan and motor is also convenient.

4-way Cassette Indoor Unit

• Strong and balanced airflow

Unit features auto operation, 4-way airflow, 7 fan speeds and strong circulating airflow.

• Ultra-low noise operation

DC inverter motor can realize stepless speed regulation to lower noise. Indoor unit can be set to work under auto quiet mode via wired controller.

Intelligent drainage device

Water height difference up to 1.0m, which can effectively drain out condensing water and save space.

DC inverter motor

With good speed regulation performance, motor efficiency improved by 30% v.s. normal motor.

Protection function

Water overflow protection, anti-freezing protection, temperature sensor malfunction protection, fan motor overload protection.

Compact 4-way Cassette Indoor Unit

• Compact Design for Easy Installation Units maintain the uniform length and width with consistent ceiling opening and panel dimension, convenient for design and installation;

• Ultra-low noise operation

DC inverter motor can realize stepless speed regulation to lower noise. Indoor unit can be set to work under auto quiet mode via wired controller.

• Intelligent drainage device

Water height difference up to 1.0m, which can effectively drain out condensing water and save space.

2-way Cassette Indoor Unit

Beautiful Appearance

With beautiful and elegant front panel, it is congenial to the indoor surroundings.

• Intelligent drainage device

Water height difference up to 1.0m, which can effectively drain out condensing water and save space.

• Two-way air flow design Two-way air outlet, to stretch air outlet distance and solve air supply problem of elongated room

Multiple protections

Anti-freezing protection, temperature malfunction protection, fan motor overload and humidity sensor protection.

1-way Cassette Indoor Unit

• Small installation space With 185mm ultrathin design, unit can be installed in the ceiling of 19cm deep.

• Detachable grille and long life filter

Grille is detachable for easy cleaning. With durable filter, cleaning cycle is 20 times longer.

• High drain pump lift

Drain pump lift reaches 1.0m, which can effectively drain out water.

Protection function

Water overflow protection, anti-freezing protection, fan motor overload protection, temperature sensor malfunction protection.

Vall-mounted Indoor Unit

Floor Ceiling Type Indoor Unit

Comfortable and balanced airflow, up&down air outlet

Up air outlet: In cooling, cool air blows out horizontally and then gradually drops. Down air swing: In heating, warm air blows downward and then gradually climbs up.

• Triple defenders for better purification

Mildew-proof filter, electrostatic fibre and anti-biotic fibre adopted to remove dust, smell, bacteria and mildew.

Cold air prevention design

During heating in winter, cold air prevention function is enabled so that air won't be blown out until it's warm.

• Multiple protections

Anti-freezing protection, temperature sensor malfunction protection, fan motor overload protection.

• Hoisted or seated, flexible installation Unit can be hoisted or seated. When seated, suspended ceiling is not needed.

Beautiful appearance

With beautiful and elegant front panel, it is congenial to the indoor surroundings.

Protection function

Anti-freezing protection, temperature sensor malfunction protection, fan motor overload protection.

• Horizontal and vertical air swing

Wider air swing range for your comfortable working and living environment.

Console Indoor Unit

Floor Standing Indoor Unit

Multiple fan speed

The fan can operate in multiple speed and satisfy different air flow volume requirements.

• Detachable grille and long life filter

Grille is detachable for easy cleaning. With long life filter, cleaning cycle is 20 times longer.

• High drain pump lift Drain pump lift reaches 1.0m, which can effectively drain out water.

Protection function

Water overflow protection, anti-freezing protection, fan motor overload protection, temperature sensor malfunction protection, auxiliary electric heating overheat protection(This function is not included in pure heat pump unit). Wide Application
 It can be widely adopted in hotels, restaurants, office, etc.

• Auto clean to ensure a healthy life

After turning off the unit, the indoor fan will keep running in low speed for a moment to dry the inner components and parts, in order to prevent mildew and keep user healthy.

Fresh Air Processing Indoor Unit

Airflow volume: 1200~4000m³/h Applicable range: Residential houses, villas, business buildings, hotels, apartments, etc.

One system, two functions

 Adopted with DC inverter technology, Fresh Air DC Inverter Multi VRF System features air conditioning function and fresh air function.

Enjoy fresh air

- Airflow volume: 1200~4000m³/h, cooling capacity: 14-45kW Applicable for all kinds of structure.
- Direct evaporative cooling adopted, air conditioning+fresh air can be realized accurately and precisely.
- DC inverter technology adopted, constant humidity is enabled with less power consumption.
- Integrated system control with Inventor INV2 Multi VRF System.

Air conditioning and fresh air, two in one

Less investment

Fresh Air DC Inverter Multi VRF System can be combined with Inventor INV2. For a same room, if the same amount of fresh air is to be taken, then the cost of INV2 +Fresh air unit is equivalent to the cost of INV2+Air exchange fan.

Less operation cost

Unit can control refrigerant output according to actual needs to ensure constant airflow temperature. By adjusting power output, light-load but high power operation can be avoided. Thus, operation cost can be greatly reduced.

Less installation space

Save installation space for outdoor units. Especially suitable for places that have restricted installation space.

Air Handler

Highly Flexible Installation

The unit is designed for outdoor installation and less indoor space taking, allowing easy installation and maintenance. The unit can be installed on the ground or on the roof of the building, which means the installation is totally flexible depending on the project requirement.

Cold Air Prevention Design

When heating in winter, cold air prevention function is enabled so that air won't be blown out until it's warm.

Long life and Washable Filter

The filter is easy to be dismantled and installed. You can use dust collector or water to clear away the dust.

Indoor Units Lineup

Specifications of Indoor Units

High Static Pressure Duct Type Indoor Unit

	Model		INV2-56HDP1S	INV2-63HDP1S	INV2-71HDP1S	INV2-80HDP1S	INV2-90HDP1S	
Constrait	Cooling	kW	5.6	6.3	7.1	8.0	9.0	
Capacity	Heating	kW	6.3	7.1	8.0	9.0	10.0	
Power supply		V/Ph/Hz		220~240/1/50 &	208~230/1/60			
Power consum	ption	W	120	120	130	130	200	
Alefferriselitere	110540.5	m ³ /h	1000/800/600	1000/800/600	1100/900/700	1100/900/700	1700/1450/1100	
Almow volume	(H/W/L)	CFM	590/471/355	590/471/355	650/530/410	650/530/410	1000/853/650	
	Cooling	A	0.6	0.6	0.6	0.6	1.0	
Rated Current ²	Heating	A	0.6	0.6	0.6	0.6	1.0	
	Water Heating	A	1 1		1	1	1	
ESP		Pa		70/0~	100			
Sound pressure	e level(H/M/L)	dB(A)	44/40/36	44/40/36	45/41/37	45/41/37	46//44/42	
Connecting pipe	Liquid	mm	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	
diameter	Gas	mm	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9	
Drain nine	External dia.	mm	Φ25	Φ25	Φ25	Φ25	Φ25	
orain pipe	Thickness	mm	2.5	2.5	2.5	2.5	2.5	
Dimension	Outline	mm		1271x55	8x268		1229x775x290	
WxDxH)	Package	mm		1348x59	7x283		1338x877x305	
Net weight/Gro	ss weight	kg	35/40	35/40	35/40	35/40	47/54	
oading	40' GP	set	192	192	192	192	128	
oading	40' HQ	set	216	216	216	216	128	

	Model		INV2-100HDP1S	INV2-112HDP1S	INV2-125HDP1S	INV2-140HDP1S	INV2-160HDP1S	INV2-224HDP1S	INV2-280HDP1S
0	Cooling	kW	10.0	11.2	12.5	14.0	16.00	22.4	28.0
Capacity	Heating	kW	11.2	12.5	14.0	16.0	18.00	25.0	31.0
Power supply		V/Ph/Hz		220~240/1/50 8	& 208~230/1/60		220~240/1/50/60	220~240/1/50 8	208~230/1/60
Power consum	otion	W	200	200	220	220	560	800	900
Alefferreitenet	110.00 5	m ³ /h	1700/1450/1100	1700/1450/1100	2000/1550/1200	2000/1700/1400	3100	4000	4400
Airriow volume	H/M/L)	CFM	1000/853/650	1000/853/650	1175/912/706	1175/1000/824	1824	2355	2590
	Cooling	A	1.0	1.0	1.0	1.0	4	4.1	4.6
Rated Current ²	Heating	А	1.0	1.0	1.0	1.0	4	4.1	4.6
Naleu Guileni	Water Heating	A	1	1	1	1	1	1	1
ESP	Pa 70/0~100 50 150/		150/50~200	150/50~200					
Sound pressure	e level(H/M/L)	dB(A)	46//44/42	46//44/42	48/45/42	48/46/44	55.0	54.0	55.0
Connecting pipe	Liquid	mm	Φ9.52	Φ9.52	Φ9.52	Φ9.52	φ9.52	Φ9.52	Φ9.52
diameter	Gas	mm	Φ15.9	Φ15.9	Φ15.9	Φ15.9	φ19	Φ22.2	Φ22.2
Drain nine	External dia.	mm	Φ25	Φ25	Φ25	Φ25	Ф30	Ф30	Ф30
Draintpipe	Thickness	mm	2.5	2.5	2.5	2.5	1.5	1.5	1.5
Dimension	Outline	mm		1229x7	75x290		1497x799x389	1483×791×385	1686x870x450
(WxDxH)	Package	mm		1338x8	77x305		1578x883x400	1758×883×470	1788x988x580
Net weight/Gro	ss weight	kg	47/54	47/54	47/54	47/54	79/103	82/104	105/140
Loading	40' GP	set	128	128	128	128	75	65	52
Loading	40' HQ	set	128	128	128	128	75	65	52

Low Static Pressure Duct Type Indoor Unit

	Model		INV2-22LD P1S	INV2-25LD P1S	INV2-28LD P1S	INV2-32LD P1S	INV2-36LD P1S
Connection	Cooling	kW	2.2	2.5	2.8	3.2	3.6
Capacity	Heating	kW	2.5	2.8	3.6	3.6	4.0
Power supply		V/Ph/Hz			220~240/1/50 & 208~230/1/60		
Power consum	ption	W	35	35	35	43	43
A1.0	(1)(8.40 S	m ³ /h	450/350/250	450/350/250	450/350/250	550/450/350	550/450/350
Almow volume	(H/W/L)	CFM	265/206/147	265/206/147	265/206/147	325/265/206	325/265/206
	Cooling	A	0.2	0.2	0.2	0.2	0.2
Rated Current ²	Heating	A	0.2	0.2	0.2	0.2	0.2
	Water Heating	A	1	1	I	1	1
ESP Pa					15/0~30	No. Vit	
Sound pressure	e level(H/M/L)	dB(A)	31/28/25	31/28/25	31/28/25	32/30/27	32/30/27
Connecting pipe	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35
diameter	Gas	mm	Φ9.52	Φ9.52	Φ9.52	Φ12.7	Φ12.7
Drain aina	External dia.	mm	25	25	25	25	25
Diain pipe	Thickness	mm	2.5	2.5	2.5	2.5	2.5
Dimension	Outline	mm			700 x 615 x 200		
(WxDxH)	Package	mm			893x743x305		
Net weight/Gro	ss weight	kg	22/27	22/27	22/27	22/28	22/28
Loading	40' GP	set	192	192	192	192	192
	40' HQ	set	192	192	192	192	192

2. ·			
Conceitu	Cooling		
Capacity	Heating		
Power supply		V	
Power consum	ption		
Airflow volume	(H/M/L)		
, and to dame	(ranse)		
	Cooling		
Rated Current ²	Heating		
	Water Heating		
ESP			

	Model		INV2-40LD P1S	INV2-45LD P1S	INV2-50LD P1S	INV2-56LD P1S	INV2-63LD P1S	
Course it is	Cooling	kW	4.0	4.5	5.0	5.6	6.3	
Japacity	Heating	kW	4.5	4.5 5.0 5.6		6.3	7.1	
Power supply		V/Ph/Hz			220~240/1/50 & 208~230/1/6	0		
Power consum	otion	W	52	52	52	99	99	
A left excerning a leave of	TIMAN S	m ³ /h	700/600/450	700/600/450	700/600/450	1000/800/600	1000/800/600	
Aniow volume(H/W/L)	CFM	410/355/265	410/355/265	410/355/265	590/471/355	590/471/355	
	Cooling	A	0.3	0.3	0.3	0.5	0.5	
Rated Current ²	Heating	A	0.3	0.3	0.3	0.5	0.5	
	Water Heating	A	1	1	1	1	1	
ESP		Pa			15/0~30			
Sound pressure	e level(H/M/L)	dB(A)	33/31/28	33/31/28	33/31/28	35/33/30	35/33/30	
Connecting pipe	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	
diameter	Gas	mm	Φ12.7	Φ12.7	Φ12.7	Φ15.9	Φ15.9	
Drain nine	External dia.	mm	25	25	25	25	25	
orain pipe	Thickness	mm	2.5	2.5	2.5	2.5	2.5	
Dimension	Outline	mm		900 x 615 x 200		1100 x	615 x 200	
WxDxH)	Package	mm		1123x743x305		1323x743x305		
Net weight/Gro	ss weight	kg	27/33	27/33	27/33	31/38	31/38	
oading	40' GP	set	192	192	192	162	162	
	40' HQ	set	192	192	192	162	162	

	Model		INV2-71LD P1S	INV2-80LD P1S	INV2-90LD P1S	INV2-100LD P1S	INV2-112LD P1S	INV2-125LD P1S	INV2-140LD P15
Consolite	Cooling	kW	7.1	8.0	9.0	10.0	11.2	12.5	14.0
Capacity	Heating	kW	8.0	9.0	10.0	11.2	12.5	14.0	16.0
Power supply		V/Ph/Hz			220-	-240/1/50 & 208~230/	1/60		
Power consum	ption	W	105	140	209	209	209	230	230
Airflow volume(H/M/L)		m³/h	1000/800/600	1100/1000/800	1500/1250/950	1500/1350/1000	1700/1500/1100	2000/1500/1150	2000/1500/1150
		CFM	590/471/355	650/590/471	885/736/599	885/795/590	1000/885/650	1175/885/677	1175/885/677
	Cooling	A	0.5	0.7	1.0	1.0	1.0	1.1	1.1
Rated Current ²	Heating	A	0.5	0.7	1.0	1.0	1.0	1.1	1.1
	Water Heating	A	1	1	1	1	1	1	1
ESP		Pa				30/0~50			
Sound pressur	e level(H/M/L)	dB(A)	35/33/30	36/34/31	40/36/32	40/36/32	40/36/32	42/40/37	42/40/37
Connecting pipe	e Liquid	mm	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52
diameter	Gas	mm	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9
Drain nine	External dia.	mm	25	25	25	25	25	25	25
Drain pipe	Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5	2.5
Dimension	Outline	mm	1200 x 65	55 x 260			1340 x 65	55 x 260	
(WxDxH)	Package	mm	1448x85	58x315			1591x86	31x330	
Net weight/Gro	ss weight	kg	40/47	40/47	46/55	46/55	46/55	47/56	47/56
Loading	40' GP	set	96	96	78	78	78	78	78
roading	40' HQ	set	96	96	78	78	78	78	78

Slim Duct Type Indoor Unit

	Model		INV2-22SD1S*	INV2-25SD1S*	INV2-28SD1S*	INV2-32SD1S*	INV2-36SD1S		
Constant .	Cooling	kW	2.2	2.5	2.8	3.2	3.6		
Capacity	Heating	kW	2.5	2.5 2.8 3.2		3.6	4.0		
Power supply		V/Ph/Hz			220~240/1/50 & 208~230/1/60)			
Power consum	ption	W	25	25	25	30	30		
Airflow volume(H/M/L)		m ³ /h	450/400/320	450/400/320	450/400/320	550/450/340	550/450/340		
		CFM	265/235/188	265/235/188	265/235/188	324/265/200	324/265/200		
	Cooling	A	0.2	0.2	0.2	0.3	0.3		
lated Current ²	Heating	A	0.2	0.2	0.2	0.3	0.3		
	Water Heating	A	1	1	1	1	1		
ESP	SP Pa 0/15								
Sound pressur	e level(H/M/L)	dB(A)	30/28/22	30/28/22	30/28/22	31/29/25	31/29/25		
Connecting pipe	e Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35		
diameter	Gas	mm	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ12.7		
Drain nine	External dia.	mm	25	25	25	25	25		
Drain pipe	Thickness	mm	2.5	2.5	2.5	2.5	2.5		
Dimension	Outline	mm			710x450x200				
(WxDxH)	Package	mm		1003x551x285					
Net weight/Gro	ss weight	kg	18.5/22	18.5/22	18.5/22	19.5/23	19.5/23		
Loading	40' GP	set	352	352	352	352	352		
Loading	40' HQ	set	352	352	352	352	352		

	Model		INV2-40SD1S*	INV2-45SD1S*	INV2-50SD1S*	INV2-56SD1S*	INV2-63SD1S*	INV2-72SD1S*		
Conneitu	Cooling	kW	4.0	4.5	5.0	5.6	6.3	7.2		
Capacity	Heating	kW	4.5	5.0	5.6	6.3	7.0	8.0		
Power supply		V/Ph/Hz			220~240/1/50 8	208~230/1/60				
Power consum	ption	W	35	35	35	45	45 50			
		m ³ /h	750/660/540	750/660/540	750/660/540	850/700/610	850/700/610	1100/800/640		
Airflow volume(H/M/L)		CFM	441/388/318	441/388/318	441/388/318	500/412/359	500/412/359	647/471/377		
	Cooling	A	0.3	0.3	0.3	0.3	0.3	0.5		
Rated Current ²	Heating	A	0.3	0.3	0.3	0.3	0.3	0.5		
	Water Heating	A	1	1	1	1	1	1		
ESP		Pa			0/*	15				
Sound pressure	e level(H/M/L)	dB(A)	33/30/27	33/30/27	33/30/27	35/33/29	35/33/29	37/34/30		
Connecting pipe	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9,52		
diameter	Gas	mm	Ф12.7	Φ12.7	Φ12.7	Φ15.9	Φ15.9	Φ15.9		
Denin alian	External dia.	mm	25	25	25	25	25	25		
Urain pipe	Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5		
Dimension	Outline	mm	07.000	1010x4	50x200	7100010	1010x450x200	1310x450x200		
(WxDxH)	Package	mm		1303x5	51x285		1303x551x285	1603x551x285		
Net weight/Gross weight k		kg	23.5/28	23.5/28	23.5/28	24.5/29	24.5/29	30.5/36		
	40' GP	set	288	288	288	288	288	224		
Loading	40' HQ	set	288	288	288	288	288	224		
lata										

* This series is without water pump.

4-way Cassette Indoor Unit

	M	odel		INV2-28FC1S	INV2-36FC1S	INV2-45FC1S	INV2-50FC1S	INV2-56FC1S	INV2-63FC1S	INV2-71FC1S
Connaite		Cooling	kW	2.8	3.6	4.5	5.0	5.6	6.3	7.1
Capacity		Heating	kW	3.2	4.0	5.0	5.6	6.3	7.1	8.0
Power supp	oly		V/Ph/Hz			220~24	0/1/50 & 208~230/1	/60		
Power cons	Power consumption		W	48	48	48	50	59	59	68
A			m ³ /h	750/650/550	750/650/550	750/650/550	830/650/550	1000/900/750	1000/900/750	1180/950/850
Almow volu	ime(H/M/L)		CFM	440/383/325	440/383/325	440/383/325	490/383/325	590/530/440	590/530/440	695/559/550
		Cooling	A	0.2	0.2	0.2	0.2	0.3	0.3	0.3
Rated Curre	ent ²	Heating	A	0.2	0.2	0.2	0.2	0.3	0.3	0.3
		Water Heating	A	1	1	1	1	1	1	1
Sound pres	sure level(H/M	/L)	dB(A)	36/34/31	36/34/31	36/34/31	36/34/31	37/35/32	37/35/32	38/36/33
Connecting	pipe	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52
diameter		Gas	mm	Φ9.52	Φ12.7	Φ12.7	Φ12.7	Φ15.9	Φ15.9	Φ15.9
Drain nina		External dia.	mm	25	25	25	25	25	25	25
Drain pipe		Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5	2.5
	Dimension	Outline	mm	840x840x190	840x840x190	840x840x190	840x840x190	840x840x240	840x840x240	840x840x240
Main Body	(WxDxH)	Package	mm	963x963x272	963x963x272	963x963x272	963x963x272	963x963x325	963x963x325	963x963x325
	Net weight/G	Gross weight	kg	22.5/29.5	22.5/29.5	22.5/29.5	22.5/29.5	26.5/34.5	26.5/34.5	26.5/34.5
	Dimension	Outline	mm	950x950x65	950x950x65	950x950x65	950x950x65	950x950x65	950x950x65	950x950x65
Panel	(WxDxH)	Package	mm	1033x1038x133	1033x1038x133	1033x1038x133	1033x1038x133	1033x1038x133	1033x1038x133	1033x1038x133
	Net weight/G	bross weight	kg	7/11	7/11	7/11	7/11	7/11	7/11	7/11
Loading du	antity	40'GP	set	167	167	167	167	140	140	140
Louging du	unity	40'HQ	set	171	171	171	171	156	156	156

	M	odel		INV2-80FC1S	INV2-90FC1S	INV2-100FC1S	INV2-112FC1S	INV2-125FC1S	INV2-140FC1S	INV2-160FC1S
0		Cooling	kW	8.0	9.0	10.0	11.2	12.5	14.0	16.0
Capacity		Heating	kW	9.0	10.0	11.2	12.5	14.0	16.0	17.5
Power supp	bly		V/Ph/Hz			220~24	0/1/50 & 208~230/1	/60		
Power cons	sumption		W	68	98	98	110	110	110	130
Airflouruphu	m ³ /h		m ³ /h	1180/950/850	1500/1350/1100	1500/1350/1100	1700/1400/1100	1860/1500/1150	1860/1500/1150	2100/1700/1400
Altiow volu	me(H/W/L)		CFM	695/559/550	880/795/650	880/795/650	1000/824/650	1095/880/677	1095/880/677	1235/1000/824
		Cooling	A	0.3	0.4	0.4	0.5	0.5	0.5	0.6
Rated Curre	ent ²	Heating	A	0.3	0.4	0.4	0.5	0.5	0.5	0.6
		Water Heating	Α	1	1	1	1	1	1	1
Sound pres	sure level(H/M	/L)	dB(A)	38/36/33	40/37/35	40/37/35	41/38/36	43/41/38	43/41/38	47/44/42
Connecting	pipe	Liquid	mm	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52
diameter		Gas	mm	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ19.05
Drain nine		External dia.	mm	25	25	25	25	25	25	25
Drain pipe		Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5	2.5
	Dimension	Outline	mm	840x840x240	840x840x320	840x840x320	840x840x320	840x840x320	840x840x320	910×910×293
Main Body	(WxDxH)	Package	mm	963x963x325	963x963x409	963x963x409	963x963x409	963x963x409	963x963x409	1023×993×375
	Net weight/G	Bross weight	kg	26.5/34.5	32.5/40.0	32.5/40.0	32.5/40.0	32.5/40.0	32.5/40.0	46.5/56.5
	Dimension	Outline	mm	950x950x65	950x950x65	950x950x65	950x950x65	950x950x65	950x950x65	1040x1040x65
Panel	(WxDxH)	Package	mm	1033x1038x133	1033x1038x133	1033x1038x133	1033x1038x133	1033x1038x133	1033x1038x133	1137x1137x140
	Net weight/G	Gross weight	kg	7/11	7/11	7/11	7/11	7/11	7/11	7.5/11.5
Loading qu	antity	40'GP	set	140	104	104	104	104	104	144
Louning do	anny	40'HQ	set	156	119	119	119	119	119	144

Compact 4-way Cassette Indoor Unit

	M	odel		INV2-22FCC1S	INV2-28FCC1S	INV2-36FCC1S	INV2-45FCC1S	INV2-50FCC1S	INV2-56FCC1S
Constant		Cooling	kW	2.2	2.8	3.6	4.5	5	5.6
Capacity		Heating	kW	2.5	3.2	4	5	5.6	6.3
Power supp	bly		V/Ph/Hz			220~240/1/50 8	208~230/1/60	1	
Power cons	sumption		W	35	35	35	45	45	45
A 140		m³/h	600/500/400	600/500/400	600/500/400	700/600/480	700/600/480	700/600/480	
Almow volume(H/M/L)		CFM	355/295/235	355/295/235	355/295/235	410/355/283	410/355/283	410/355/283	
		Cooling	A	0.4	0.4	0.4	0.5	0.5	0.5
Rated Curre	mt ²	Heating	A	0.4	0.4	0.4	0.5	0.5	0.5
		Water Heating	A	1	1	1	1	1	1
Sound pres	sure level(H/M	level(H/M/L) dB(A) 46/39/35 46/39/35 46/39/35 47/43/38 47/43/38			47/43/38				
Connecting	pipe	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52
diameter		Gas	mm	Φ9.52	Φ9.52	Φ12.7	Φ12.7	Φ12.7	Φ15.9
Drain nina		External dia.	mm	25	25	25	25	25	25
Diairipipe		Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5
	Dimension	Outline	mm	596x596x240	596x596x240	596x596x240	596x596x240	596x596x240	596x596x240
Main Body	(WxDxH)	Package	mm	773×733×300	773×733×300	733x733x300	733x733x300	733x733x300	733x733x300
	Net weight/G	iross weight	kg	20.5/25.5	20.5/25.5	20.5/25.5	20.5/25.5	20.5/25.5	20.5/25.5
	Dimension	Outline	mm	650x650x50	650x650x50	650x650x50	650x650x50	650x650x50	650x650x50
Panel	(WxDxH)	Package	mm	763x763x105	763x763x105	763x763x105	763x763x105	763x763x105	763x763x105
	Net weight/G	iross weight	kg	3.5/5.0	3.5/5.0	3.5/5.0	3.5/5.0	3.5/5.0	3.5/5.0
Loading due	aptity	40'GP	set	267	267	267	267	267	267
Loading da	annity	40'HQ	set	288	288	288	288	288	288

2-way Cassette Indoor Unit

	M	odel		INV2-28DC 1S	INV2-36DC 1S	INV2-45DC 1S	INV2-50DC 1S	INV2-56DC 1S	INV2-63DC 1S	INV2-71DC 1S
0		Cooling	kW	2.8	3.6	4.5	5.0	5.6	6.3	7.1
Capacity Power suppi Power const Airflow volur Rated Currer Sound press Connecting p diameter Drain pipe Main Body Panel		Heating	kW	3.2	4.0	5.0	5.6	6.3	7.1	8.0
Power supp	ily	<i>h</i>	V/Ph/Hz			220~24	40/1/50 & 208~230/1	1/60		
Power cons	umption W 55.0 55.0 55.0 55.0 103.0 103.0		103.0	103.0						
Airflauriahu	A- W		m³/h	830/600/530	830/600/530	830/600/530	830/600/530	1100/820/760	1100/820/760	1100/820/760
All llow volu	(H/W/L)		CFM	490/355/312	490/355/312	490/355/312	490/355/312	650/483/647	650/483/647	650/483/647
		Cooling	A	0.3	0.3	0.3	0.3	0.7	0.7	0.7
Rated Curre	nt ²	Heating	A	0.3	0.3	0.3	0.3	0.7	0.7	0.7
		Water Heating	A	1	1	1	/	1	1	1
Sound pres	sure level(H/M	/L)	dB(A)	35/33/31	35/33/31	35/33/31	35/33/31	39/37/35	39/37/35	39/37/35
Connecting	pipe	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52
diameter		Gas	mm	Φ9.52	Φ12.7	Φ12.7	Φ12.7	Φ15.9	Φ15.9	Φ15.9
Drain nina		External dia.	mm	25	25	25	25	25	25	25
Drain pipe		Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5	2.5
	Dimension	Outline	mm	1200x520x315	1200x520x315	1200x520x315	1200x520x315	1200x520x315	1200x520x315	1200x520x315
Main Body	(WxDxH)	Package	mm	1520x655x415	1520x655x415	1520x655x415	1520x655x415	1520x655x415	1520x655x415	1520x655x415
	Net weight/G	Bross weight	kg	40.5/52.5	40.5/52.5	40.5/52.5	40.5/52.5	43.0/55.0	43.0/55.0	43.0/55.0
	Dimension	Outline	mm	1443x630x33	1443x630x33	1443x630x33	1443x630x33	1443x630x33	1443x630x33	1443x630x33
Panel	(WxDxH)	Package	mm	1575x765x105	1575x765x105	1575x765x105	1575x765x105	1575x765x105	1575x765x105	1575x765x105
	Net weight/G	Bross weight	kg	7.0/11.0	7.0/11.0	7.0/11.0	7.0/11.0	7.0/11.0	7.0/11.0	7.0/11.0
Loading qu	antity	40'GP	set	101	101	101	101	101	101	101
Locality que	annay	40'HQ	set	115	115	115	115	115	115	115

1-way Cassette Indoor Unit

	M	odel		INV2-22SC1S	INV2-28SC1S	INV2-36SC1S	INV2-45SC1S	INV2-50SC1S
Concernite of		Cooling	kW	2.2	2.8	3.6	4.5	5.0
Capacity		Heating	kW	2.5	3.2	4.0	5.0	5.6
Power supply V/Ph/H		V/Ph/Hz		2	20~240/1/50 & 208~230/1/6	60		
Power cons	umption		W	30	30	30	45	45
			m ³ /h	600/500/450	600/500/450	600/500/450	830/600/500	830/600/500
AITTIOW VOIU	me(H/M/L)		CFM	355/295/265	355/295/265	355/295/265	490/355/295	490/355/295
		Cooling	A	0.2	0.2	0.2	0.3	0.3
Rated Curre	nt ²	Heating	A	0.2	0.2	0.2	0.3	0.3
		Water Heating	A	1	1	1	1	1
Sound pres	sure level(H/M	/L)	dB(A)	36/32/28	36/32/28	36/32/28	40/35/30	40/35/30
Connecting	pipe	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35
diameter		Gas	mm	Φ9.52	Φ12.7	Φ12.7	Φ12.7	Φ12.7
Desis sins		External dia.	mm	25	25	25	25	25
Drain pipe		Thickness	mm	2.5	2.5	2.5	2.5	2.5
	Dimension	Outline	mm	987x385x178	987x385x178	987x385x178	987x385x178	987x385x178
Main Body	(WxDxH)	Package	mm	1307x501x310	1307x501x310	1307x501x310	1307x501x310	1307x501x310
	Net weight/G	Gross weight	kg	20.0/27.0	20.0/27.0	20.0/27.0	21.0/28.5	21.0/28.5
	Dimension	Outline	mm	1200x460x55	1200x460x55	1200x460x55	1200x460x55	1200x460x55
Panel	(WxDxH)	Package	mm	1265x536x118	1265x536x118	1265x536x118	1265x536x118	1265x536x118
	Net weight/G	Bross weight	kg	4.2/6.0	4.2/6.0	4.2/6.0	4.2/6.0	4.2/6.0
Loading aux	antitu	40'GP	set	138	138	138	138	138
Loading day	annty	40'HQ	set	138	138	138	138	138

Wall-mounted Type Indoor Unit

	Model		INV2- 22W1S*	INV2- 28W1S*	INV2- 36W1S*	INV2- 45W1S*	INV2- 50W1S*	INV2- 56W1S*	INV2- 63W1S*	INV2- 71W1S*
	Cooling	kW	2.2	2.8	3.6	4.5	5.0	5.6	6.3	7.1
Capacity	Heating	kW	2.5	3.2	4.0	5.0	5.8	6.3	7.0	7.5
Power supply		V/Ph/Hz				220~2	240/1/50			
Power consum	ption	W	50	50	60	60	60	70	70	70
A:		m ³ /h	500/420/350	500/420/350	630/550/480	630/550/480	630/550/480	750/600/500	750/600/500	750/600/500
Airtiow volume	H/M/L)	CFM	294/247/206	294/247/206	371/324/282	371/324/282	371/324/282	441/353/294	441/353/294	441/353/294
	Cooling	A	0.2	0.2	0.31	0.31	0.31	0.31	0.31	0.31
Rated Current ²	Heating	A	0.2	0.2	0.31	0.31	0.31	0.31	0.31	0.31
	Water Heating	A	1	1	1	1	1	1	1	1
Sound pressure	e level(H/M/L)	dB(A)	38/34/30	38/34/30	44/41/38	44/41/38	44/41/38	44/41/38	44/41/38	44/41/38
Connecting pipe	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6,35	Φ9.52	Φ9.52	Φ9.52
diameter	Gas	mm	Φ9.52	Φ9.52	Φ12.7	Φ12.7	Ф12.7	Φ15.9	Φ15.9	Φ15.9
Drain nine	External dia.	mm	Φ20	Ф20	Φ20	Φ20	Φ20	Ф30	Ф30	Ф30
brain pipe	Thickness	mm	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Dimension	Outline	mm	843x18	80x275		940x200x298			1008x221x319	
(WxDxH)	Package	mm	973x25	58x370		1068x288x395			1131x398x328	
Net weight/Gro	ss weight	kg	10/12.5	10/12.5	12.5/15.5	12.5/15.5	12.5/15.5	15/18.5	15/18.5	15/18.5
Loading	40' GP	set	702	702	557	557	557	441	441	441
Loading	40' HQ	set	819	819	624	624	624	503	503	503

Note: * This series is without water pump.

Floor Ceiling Type Indoor Unit

	Model		INV2- 28K1S	INV2- 36K1S	INV2- 50K1S	INV2- 63K1S	INV2- 71K1S	INV2- 90K1S	INV2- 112K1S	INV2- 125K1S	INV2- 140K1S
Connector	Cooling	kW	2.8	3.6	5.0	6.3	7.1	9.0	11.2	12.5	14.0
Capacity	Heating	kW	3.2	4.0	5.6	7.1	8.0	10.0	12.5	14.0	16.0
Power supply		V/Ph/Hz			10	220~240/1/50	0 & 208~230/1/6	D			
Power consum	otion	W	40	40	50	75	75	140	160	160	160
41.0		m³/h	650/580/500	650/580/500	950/850/700	1400/1150/1000	1400/1150/1000	1600/1400/1200	2000/1800/1450	2000/1800/1450	2000/1800/1450
Aimow volume	H/M/L)	CFM	380/341/294	380/341/294	560/500/410	825/677/590	825/677/590	940/824/706	1175/1059/853	1175/1059/853	1175/1059/853
	Cooling	A	0.2	0.2	0.25	0.38	0.38	0.7	0.95	0.95	0.95
Rated Current ²	Heating	A	0.2	0.2	0.25	0.38	0.38	0.7	0.95	0.95	0.95
	Water Heating	A	1	I.	/	1	/	1	1	1	1
Sound pressure	e level(H/M/L)	dB(A)	36/34/32	36/34/32	42/38/33	44/42/39	44/42/39	50/47/43	51/47/42	52/49/45	52/49/45
Connecting pipe	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52
diameter	Gas	mm	Φ9.52	Φ12.7	Ф12.7	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9
Drain nine	External dia.	mm	Φ17	Φ17	Φ17	Φ17	Φ17	Φ17	Φ17	Φ17	Φ17
Drain pipe	Thickness	mm	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75
Dimension	Outline	mm		1220x700x225			1420x700x245			1700x700x245	
(WxDxH)	Package	mm		1343x823x315			1548x828x345			1828x828x345	
Net weight/Gro	ss weight	kg	40/49	40/49	40/49	50/58	50/58	50/58	60/68	60/68	60/68
Loading	40' GP	set	145	145	145	90	90	90	84	84	84
Loading	40' HQ	set	158	158	158	98	98	98	98	98	98

Console Indoor Unit

	Model		INV2-22C1S	INV2-28C1S	INV2-36C1S	INV2-45C1S	INV2-50C1S
	Cooling	kW	2.2	2.8	3.6	4.5	5.0
Capacity	Heating	kW	2.5	3.2	4.0	5.0	5.5
Power supply		V/Ph/Hz	2000	2	220-240/1/50 & 208-230/1/60		
Power consum	otion	W	15	15	20	40	40
Airflourischumol	10.40.5	m³/h	400/320/270	400/320/270	480/400/310	680/600/500	680/600/500
Airilow volume(H/W/L)	CFM	235/188/159	235/188/159	282/235/182	400/353/294	400/353/294
	Cooling	A	0.15	0.15	0.15	0.15	0.15
Rated Current ²	Heating	A	0.15	0.15	0.15	0.15	0.15
	Water Heating	A	1	1	1	/	/
ESP		Pa	0	0	0	0	0
Sound pressure	level(H/M/L)	dB(A)	38/33/27	38/33/27	40/37/32	46/43/39	46/43/39
Connecting pipe	Liquid	mm	6.35	6.35	6.35	6.35	6.35
diameter	Gas	mm	9.52	9.52	9.52	12.7	12.7
Drain nine	External dia.	mm	17.2	17.2	17.2	17.2	17.2
Diani pipe	Thickness	mm	1	1	1	1	1
Dimension	Outline	mm	700/215/600	700/215/600	700/215/600	700/215/600	700/215/600
(WxDxH)	Package	mm	780x285x682	780x285x682	780x285x682	780x285x682	780x285x682
Net weight/Gro	s weight	kg	16/19	16/19	16/19	16/19	16/19
oading	40' GP	set	387	387	387	387	387
Longenig	40' HQ	set	433	433	433	433	433

Floor Standing Type

Model			INV2-100FS 1S
Capacity	Cooling	kW	10
Capacity	Heating	kW	11
Power supply		V/Ph/Hz	
Power consum	ption	W	185
A: 0 1		m ³ /h	1850/1600/1400
Airflow volume	(H/W/L)	CFM	1089/942/824
Rated Current ²	Cooling	A	1.5
	Heating	A	1.5
	Water Heating	A	1
ESP		Pa	0
Sound pressur	e level(H/M/L)	dB(A)	50/48/46
Connecting pipe	Liquid	mm	9
diameter	Gas	mm	16
Drain pine	External dia.	mm	31
Diain pipe	Thickness	mm	4.5
Dimension	Outline	mm	1870x580x400
(WxDxH)	Package	mm	2083/738/545
Net weight/Gro	ss weight	kg	54/74
Loading	40' GP	set	67
Loading	40' HQ	set	67

Fresh Air Processing Indoor Unit

	Model		INV2-FAIR1401S*	INV2-FAIR2241T*	INV2-FAIR2801T*	INV2-FAIR2801T*	INV2-FAIR4501T*
0	Cooling	kW	14.0	22.4	28.0	28.0	45,0
Capacity	Heating	kW	10.0	16.0	20.0	20.0	32.0
Power supply		V/Ph/Hz	220~240/1/50		380~415	/3/50	
Power consum	ption	W	360	740	760	1060	1240
A1.0	(1.0.10 N	m ³ /h	1200	2000	2500	3000	4000
Almow volume	(H/W/L)	CFM	705	1175	1470	1765	2355
	Cooling	A	1.82	1.32	1.36	1.89	2.22
Rated Current ²	Heating	A	1.82	1.32	1.36	1.89	2.22
	Water Heating	A	1	1	1	1	1
ESP		Pa	150		200		
Sound pressur	e level(H/M/L)	dB(A)	42	47	48	51	52
Connecting pipe	e Liquid	mm	Φ9.52	Φ9,52	Φ9.52	Φ9.52	Φ12.7
diameter	Gas	mm	Φ15.9	Ф19.05	Φ22.2	Φ22.2	Φ28.6
Drain nina	External dia.	mm	25	25	25	25	25
Drain pipe	Thickness	mm	2.5	2.5	2.5	2.5	2.5
Dimension	Outline	mm	1463 x 756 x 300		1500 x 1000 x 500		1700 x 1100 x 650
(WxDxH)	Package	mm	1514x785x360		1840x1200x673		1890x1460x835
Net weight/Gro	ss weight	kg	63.5/71	130/182	134/188	134/188	208/266
loading	40' GP	set	84.0	18.0	18.0	18.0	16.0
Loading	40' HQ	set	98.0	18.0	18.0	18.0	16.0

Note: * This series can be matched with GMV5(Top discharge outdoor unit)only.

	INV2-140FS 1S	
	14	
	15	
220-240/1/50 & 208-230	0/1/60	
	185	
	1850/1600/1400	
	1089/942/824	
	1.5	
	1.5	
	1	
-1	0	
	50/48/46	
	9	
	16	
	31	
	4.5	
	1870x580x400	
	2083/738/545	
	57/77	
	67	
	67	

Control System

Smart Model Selection Software and Debugging Software

Model Selection Software

Inventor multi VRF selection software is a kind of advanced computer program for selecting models automatically in sales and project bidding. It integrates multi VRF selection logic and computer software to provide a user-friendly interactive interface, which is able to automatically recommend suitable models to user according to ambient condition of project and user's demand. It is applicable for INV2.

Flexible Setting of Project Design Conditions

When setting up a new model selection project, the information of customer, designer, unit series and working conditions, etc. can be set as relevant parameters of model selection, and then sent to data report for checking during project design.

Series (MV Serie		
or Unit GRV IV Is	n BC Lasver warter (74	ter :
date Load By		
ert Design Condit) Crailing Indeor Bry Bulb Teng Ket Bulb Teng Relative Hamidity Outdoor Bry Dulb Teng	• Coolina iensi , 27 , 19 , 45, 77 , 45, 77	e Les
Pr	roiect	De
	er Unit (DEV. IV. In clute Load By (est Devices Condit) Coding Todor Ny Bolh Tony Reliation Hand Sity Octoor Bry Bulh Tony Del Devices Pf	or buil (1997) 27 Januarian (2) aliais Leak 39 Costang Costang Ladorr Bry Babh Tang, 27 Kalatine Heak Guy 66, 77 Gordony Bry Babh Tang, 25 Project

Accurate Recommendation of Indoor Unit and Outdoor Unit

When selecting indoor unit model with the software, you can use automatic recommendation way only by inputting the required air conditioning load and indoor unit series. Then the software will recommend the suitable indoor unit model automatically according to model selection logic. When selecting outdoor unit model, you can use automatic recommendation way directly to select the suitable outdoor unit model.

(274 Series), 84104, 5061 • (ex) •	Confirmation:
C Resting Lines	The second
Resting	Bey Built (map 17 GV C Wet Built Boy 18 DV C Belt (the Mart 19 DV C)
Indeer Bry Bully Serg [20] * T.	And a state of the
Outdoor Sey Bulls Tory (2)	
and the the transfer (6	
Kalative fimility 05.36 %	
(L-\$0)T-\$0) BA	(<上-\$0) 元素 RA
CL-RUID-RUIZ LAR	

1000	A strength birty.			
Outdoor Unit				
Real Property lies				
Augustan (1997)		A Manual Abouts		Redgell of H
1.9	Autom Til			
	and the second s		12/2/2 10/10/10/10/10	
	Analyse Analysed		man second (20-1387/hard	Casi and read
	Salast Kr		Quertaniana	
	Country and S	-	Comp Lewis	
	Catalog and T	-		
	Packingh Brack to 2011			
	theodient to \$4, 2		Salarahan (C. Station)	
			General D	
	Ref to COU F			
	-304 feet inter + 001 feet at			
	-	100		
	LOBIE	CONTRACTOR OF STREET, LODIER, CONTRACT, CONTRA	Sector 1	Integral Integral
Laurent bit ma	Add Ne	w IDU (1)		
Cudoor Unit		w IDU (1)		
Cultor Unit	Add Nev (Riskur J specifier	w IDU (1)		
Cultor Unit	Add Nev (1) dealer # (2) dealer	w IDU (1)		
Cuttor Unit	Add Nev (1) dense 4 demoister bei rite (new for 1) (new for 1) (ne	w IDU (1)		-
Cuttoor Unit	Add Nev 2010/00-0 20	w IDU (1)	- k	
Cuttor Unit	Add Nev annual annua	w IDU (1)		Allow the Last's an
Cution Unit	Add Nev annotation annotatio			silana ita santa ita Silana ita
Cutoor Unit	Add Nev announces an	w IDU (1)		Automotive class:
Cuttor Unit	Add Nev	w IDU (1)		Alarah Tito (Jane) Jan Alarah Tito (Jane) Jan
Cuttor Unit	Add Nev and any and any any any any any any any any any any any any any any any any any any	w IDU (1)		Alloca Bas (Bas') Bas Alloca Tas (Bas') Bas Alloca Tas
Conjugation and the second sec	Add Nev annotation annotatio	W IDU (1)		Aller The Constants
Conference for a line	Add Nev and any and any and any and any	w IDU (1)		Allega Per Constants Allega Per Constants Allega Per Constants Allega Per Constants
	Add Nev and any and any any hard for any	w IDU (1)		Response for the second
Confect Unit	Add Nev			Allange Start Start Start Allange Start Start Start Allange Start Start Start Allange Start Start
Control to a second	Add Nev amage and any (and a final state (and a final state (and a final state (and a final state) (and a	w IDU (1)		Allenge West - Start - Start Allenge West - Start - Start Allenge West - Start - Start - Allenge West - Start - Start - Allenge West - Start - Start - Allenge West - Start - Start

Free Modification of Selected Models

If you are not satisfied with the system recommended by the software, you can select or adjust indoor unit model through alternate selection function.

Edit IDU

One-click Modification and System Validation

When reselection is needed due to major changes of indoor units, one-click recommendation function can be adopted to reselect all indoor units with simple operation; after finishing model selection, you can use one-click system validation function to check various parameters requirements of air conditioning system.

One-click Recommendation

Optional Controller Configuration and Electric System Configuration

The software will offer controller model matched with the system. The user only needs to choose controller type and then the software will output the controller model into the report.

Optional Controller Configuration

	at restance a	Removed a			
	12	A Dated (Dat			
	1				
	Bar (20)	Secto Sume Long		States - Ballio	n -
	1 MERCER		2		
		INDIA		00 00-00	
100 L		a distant for		Carlos Incidence(24)	
		fammer, 250	UPI A 3107 No.4	Laborat	A Date and
100		fateri, Sizet	80/820730-1	Tulline.	
42		Tuteri Mileti	an remained	Laborate State	diamon and
		and the second se			
101 B					
and sold		here shalls dot for last place of	behim balking alt.		
25		10.04			
		(2.002)		10.00	Lines and
-				0.00	
1000 L					
NAME OF TAXABLE					
		(*)	11.8	- 10 million - 10	

Save Model Selection Project, Output Data Report and System Wiring Diagram

After finishing system selection and various system configurations, the user can save model selection project freely for future reference. Then the user can output relevant parameters of selected project in an excel form and output system wiring CAD diagram for reference in installation.

Intelligent Debugging Software

INV2 offers an intelligent debugging software to the end-users for faster construction needs.

Monitoring Functions

- Fully control the operation status of each device of the system;
- Hover the mouse over the parameter to display its remarks.
- The online devices will be displayed in a tree structure:
- Display the information of air conditioner in divided regions;
- Each display region can be moved or concealed;
- Display updated status of units in real time;

Control Functions

- Control the operation of unit as you like;
- Comprehensive control of outdoor unit, indoor unit, water tank, hydro box, etc.;
- · Real-time display of current status or status after being controlled;
- Both single control and group control are available.

Project Debugging Functions

- One-click and automatic project debugging;
- Project debugging is arranged step by step from left to right;
- Manual intervention and skipping of some debugging phases are available.
- Green icons will be displayed for the items finishing debugging; red icons will be displayed for the items having debug exception; light yellow icons display debugging information;

-	
California (Section of Section of	😝 W. Mara Data Saray
a tot allow largest	
Contract to beer solid it I mette at	T total langung
Antoin 21 Harry and	Altered (
Contract in termination	C R hannel
💓 bas bhire hen lanssen fail	A find loans a links
Q1101-0000	R Barris Campia S. Norra
and the first factor in the second se	Access Sea Englisher
Chinese inthins here	
-	

Auto Data-Saving Function

Data will be saved automatically. Database saving path can be changed or data document can be generated repeatedly.

USB Data Converter

Users can use USB data converter to freely convert CAN/HBS/RS485 data into USB data, achieving data interchange between computer and air conditioner.

Gie Cana

Auto Direction of Connection Way

The wiring diagram will direct connection way automatically, so that the user can get the connection way quickly.

Multiple Intelligent Remote Control Management

Inventor INV2 provides multiple intelligent controls in order to satisfy all demands. It can control both a room and a building at the same time.

Visualized Management

- System has a map that can display air conditioners' locations in rooms and buildings.
- System is able to measure the status and number of air conditioners in different levels

Everyday Management

Setting for daily operation

a.Management in days/weeks/months/years b.Management in each unit c.Simple display for management

Other functions

a.Power on/off, modes, humidity, fan speed b.Waste of energy that may be caused by forgetting to turn off the air conditioner can be avoided

Group Management

• Central management in groups

a.Free choices of dividing groups b.Central control over power on/off c.Central control over temperature d.Central control over modes e.Central control over user authority

• Everyday Management at different locations a.Management for overtime working b.Management for meal breaks c.Management for working time											
5 7	9	11	13	15	17	19	21	23			
N 14 6			lunch break								
	Working	V	Vorking	time	Overtin workin	ne g					
breakfast		lunc	h break			dinne	r				
		W	orking	ime							
			- barra Roma - E	1				ہ (100) ہو ایک		0 and 40	

Authority Management

Only for indoor units

a.Limited control over power on/off b.Limited control over temperature c.Limited control over modes

Statistics Analysis

Recording statistics

System can self generate graphs of statistics for easy management and analysis.

Recording errors

System can show the information of errors in charts and send alarms of errors through emails.

Recording operation

System can record users' daily operation.

Calculating Cost of Electricity

Auto calculation according to users

a.According to the operating time, modes, flow of refrigerant, humidity and other factors, system can calculate the cost of electricity for users in different locations.

b.Detailed information of bills and operation can be provided.

Energy Management

· Analysis of energy cost

a.Air conditioners that cost much energy b.Air conditioners that are set in low temperature c.Air conditioners with bad cooling performance

Energy saving

Limits on electricity

a.Analysis on the cost of electricity b.Set the maximum cost of electricity and unit will be operating in limited conditions when the maximum number is reached.

c.System can remind users the cost of electricity during operation and give suggestions on energy saving.

Economic operation

System is able to operate under an energy-saving condition

VIP Management

System can provide independent and unique service to VIP users.

• Ways to save energy based on the following aspects:

- a.Operating time
- b.Unit is on too early
- c.Unit is off too late
- d.Comfort
- e.Cost of electricity/cost of electricity per square meter

Wired Controller and Remote Controller

There are two kinds of controllers: wired controller and remote controller. The system provides various controls for users, such as cooling, heating, dehumidifying and fan etc., users can select it flexibly according to their own using methods.

Wired controller XK46

- LCD with black background and white words; touch buttons;
- Clock can be displayed and set; 24 hours timer setting for on/off;
- 7 levels of fan speed, up & down swing and left&right swing;
- Can be switched in auto, cooling, dehumidifying, fan, heating, floor heating, 3D heating and space heating operation modes;
- Master and slave wired controllers can be set; simultaneous control over several IDUs is available;
- Available functions: sleep, ventilation, quiet/auto quiet, light, energy saving, auxiliary heating, drying, memory, low-temperature dehumidifying, absence in heating, controllable auxiliary heating in dehumidifying, filter cleaning reminder, etc.;
- Detect ambient temperature; receive infrared remote controller signal;
- With project parameters viewing and setting functions.

Remote controller YAP1F

Remote Controller YV1L1

Wired controller XK49 (For hotel)

- With simplified functions, mechanical buttons, back lighting LCD and convenient operation;
- Can be switched in auto, cooling, dehumidifying, fan and heating operation modes;
- Master and slave wired controllers can be set; simultaneous control over several IDUs is available;
- Detect ambient temperature; receive infrared remote controller signal;
- With system parameters viewing and setting functions;
- 7 levels of fan speed, up&down swing;
- Door control system can be connected.

- Can be switched in auto, cooling, dehumidifying, fan and heating operation modes;
- · Besides turbo,6 levels of fan speed can be set;
- Available functions: child lock, drying, health, ventilation, turbo, sleep, light, absence, I-feel and timer;
- Clock display and indoor/outdoor ambient temperature viewing functions;
- Up & down swing and left & right swing.

- Back lighting LCD;
- Can be switched in auto, cooling, dehumidifying, fan, heating, floor heating, 3D heating and space heating operation modes;
- 7 levels of fan speed, up&down swing and left&right swing;
- Available functions: child lock, energy saving, drying, health, ventilation, quiet/auto quiet, sleep, light, absence, low-temperature dehumidifying, l-feel and timer;
- With clock display, system parameters viewing and setting functions.

Wired controller XK55

- Elegant appearance;
- High-resolution color LCD;
- Capacitive touch control; receive infrared remote controller signal;
- Various timing functions: three weekly timers and one countdown timer can be set simultaneously; mode, temperature and fan speed can be preset in weekly timer;
- Complete system functions; each function will be implemented in an individual page with interactive and humanized interface;
- Various personalized functions, e.g. setting brightness and backlight time;
- Sufficient viewing functions, e.g. viewing on/off status and after-sales service hot line.

• Single control of one unit

Each indoor unit has an independent controller.

Central control of several indoor units

One wired controller can control as many as 16 indoor units.

• Multiple control of one unit

One indoor unit can be controlled by several wired controllers at different places.

• Joint control of remote controller and wired controller

Users can control one unit with two types of controllers: a remote controller which is convenient and flexible; or a wired controller which includes every function of an air conditioner.

Smart Zone Controller and Central Controller

Smart zone controller CE53-24/F(C)

- 1280*800 high-resolution color LCD;
- 7" capacitive touch screen for easy operation;
- Shielding function of single unit, group and all IDUs (shielding on/off, mode, temp setting, etc.);

- With various functions: centralized control(control all indoor units), group management(support DIY grouping), schedule management(setting of several schedules) and single unit control(on/off, mode, temp setting, fan speed, quiet, swing control, etc.);
- Provide naming of indoor units, selection of icons and personalized settings(setting background, backlight, etc);
- Up to 32 units can be centrally controlled;
- · Elegant and fashionable appearance;
- Embedded installation in wall with projecting thickness only of 11mm;
- Connectable with network of indoor units or outdoor units;
- Independent power supply in 110~240V wide voltage range;
- With project setting, parameter viewing, malfunction record and access management functions.

Central controller CE52-24/F(C)

		(\$7.5)			10.00.20
	•	A 1	h (A		198
-	Ren	1	an her	e Da	Al-Contr
	2 * *	A* 2	· ·	a Boom	Crock B
Aver 1	Recon	Rate O	en Der		Stream
	4	E MO MO	0	•	0

- 1280*800 high-resolution color LCD;
- 7" capacitive touch screen for easy operation;
- With project setting, parameter viewing, malfunction record and access management functions.

- With various functions: centralized control(control all indoor units), group management(support DIY grouping), schedule management(setting of several schedules) and single unit control(on/off, mode, temp setting, fan speed, quiet, swing control, etc.);
- Shielding function of single unit, group and all IDUs (shielding on/off, mode, temp setting, etc.);
- Provide naming of indoor units, selection of icons and personalized settings(setting background, backlight, etc);
- Up to 128 units can be centrally controlled;
- · Elegant and fashionable appearance;
- Embedded installation in wall with projecting thickness only of 11mm;
- Connectable with network of indoor units or outdoor units;
- Independent power supply in 110~240V wide voltage range;

BACnet Gateway

BACnet gateway kits MG30-24/D2(B) are intended to realize the data exchange between the air conditioning unit and BAS, and providing the standard BACnet/IP building interface and 8 I/O interfaces, one of which is the fire alarm signal interface. The status of the other 7 I/O interfaces is mapped to the specific objects of the BACnet/IP bus and can be defined by the user.

Applicable models: INV2 All DC Inverter Multi VRF System, INV2 DC Inverter Multi VRF System, INV2 DC Inverter Water Cooled Heat Pump Multi VRF System.

- International standard BACnet/IP interface, which has passed BTL certification;
- Real-time monitoring of unit operation status, e.g. on/off, mode, temperature;
- Real-time response to the control of unit (on/off, mode setting and speed setting, etc.) by monitoring software;
- Monitor unit errors;

- Lock unit operation statuses, directing at all control functions of unit itself or a certain setting function;
- Achieve cooling and heating temperature limitation functions;
- 8 DI/DO interfaces for receiving fire alarm signal and user's definition logic;
- Big storage capacity of unit operation data for 6 months.

Modbus Gateway

Modbus Gateway provides INV2 system with the Modbus protocol interface when connecting to the Building Management System(BMS) in order to achieve central control and remote control over GMV5 system by BMS.

Applicable models: INV2 All DC Inverter Multi VRF System, INV2 DC Inverter Multi VRF System, INV DC Inverter Water Cooled Heat Pump Multi VRF System.

- Real-time monitoring of unit operation status, e.g. on/off, mode, temperature;
- Real-time response to the control of unit (on/off, mode setting and speed setting, etc.) by monitoring software;
- Control all the units switches of on and off.
- Monitor unit errors;
- One Modbus bus can support up to 255 gateways. One Modbus gateway can support at most 16 outdoor units(up to 64 modular outdoor units) and 128 indoor units;

- Lock unit operation statuses, directing at all control functions of unit itself or a certain setting function;
- Linkage control, supporting 5 DI and 5 DO for receiving fire alarm signal and user's definition logic;
- CAN, RS485 communication ports are non-polar, convenient for construction wiring;
- Achieve cooling and heating temperature limitation functions;
- 100-240 VAC,50/60Hz wide voltage range, adapted to the power supply of each country and region.

Control System Lineup

Product series Controlling system		series	Cassette Type	(High ESP Low ESP Slim Ducted) Duct Type	Fresh Air Processing	Wall mounted Type	Floor Ceiling Type	Console Type	Floor Standing Type	Air Handler	
				٠	0	0	•	٠	٠	•	0
Wireless Controller		YV1L1		0	0	0	0	0	0	0	0
		XK46		0	•	•	0	0	0	0	•
Wir	Wired controller		2182 H	0	0	0	0	0	0	0	0
			26.18	0	0	0	0	0	0	0	0
-					0	0					
Centra	Centralized Controller			0	0	0	0	0	0	0	0
Smart .	Smart Zone Controller			0	0	0	0	0	0	0	0
Long-distance	Long-distance monitoring software			0	0	0	0	0	0	0	0
BMS Accessories	Commmunication module(modbus) GMV BACnet gateway (BACnet)	ME30-24/E4(M)		0	0	0	0	0	0	0	0
		MG30-24/D2(B)		0	0	0	0	0	0	0	0
Other	Optoelectronic isolated converter	RS232-RS422\485		0	0	0	0	0	0	0	0
modules	Optoelectronic isolated signal multiplier	RS-422\485		0	0	0	0	0	0	0	0

Note: • means standard, • means optional.

Adopt Advanced Heat Exchange Core

ERV adopts cross flow plate exchanger with air volume below 3000m3/h. Fresh air will be introduced and internal leakage is low, which effectively prevent pollution to fresh air.

Double-way Ventilation for Fresh Air

ERV can not only introduce lots of fresh air, but also discharge the stagnant air at the same time, which effectively minimizes the toxic air from the inner and other materials. The ventilation effect is very obvious, ensuring enough supply of fresh air to the indoor space.

No Cross Contamination for Ensuring Healthy Fresh Air

The unique cross-flow heat exchange valve sub-assy is adopted. There is only energy exchange between indoor air and outdoor air with little exchange of air, which effectively prevents cross contamination and "air-condition" disease.

Air flow: 350~3000m³/ h

• Energy Recovery Ventilation System can introduce the fresh air freely on the condition that all the windows closed or exhausted fan uninstalled. It can solve the problem of stagnant air effectively.

It is usually installed in the ceiling of corridor and supplies fresh air to each room through ducts.

Pretreatment of Fresh Air for Energy-saving

When fresh air is introduced, its temperature and humidity will be exchanged with the discharged warm air. As the fresh air is preheated and humidified, energy is saved and load of unit is reduced.

Energy Recovery Ventilation(ERV)

Control System Lineup

	Pro	oduct series	ERV
Control sy	rstem		O OF
Wired controller	Z5N151		•
Interface of the main board	BMS		٠
Optoelectronic isolated converter	RS232- RS422485		0
Optoelectronic isolated signal multiplier	RS-422\485		0

Note: • means standard, • means optional.

Note

Note

INVENTOR GREECE 2, Thoukididou str.,

145 65 Ag.Stefanos, Athens - Greece

INVENTOR ROMANIA Splaiul Independentei Street, no 17 101 Izvor Building, 4th entrance 5th floor, ap. 68, Area 5 050093, Bucharest - Romania

INVENTOR CHINA 15-4B, Chunshuian, No.3 Desheng Zhong Road, Daliang, Shunde, Foshan, Guangdong - China

E-mail: export@inventor.ac Tel: +30211 3003326 Fax: +30211 3003333

www.inventorairconditioner.com